



POWER TOOLS CATALOG 2017 SPRING



Flavic Tools & Equipment Inc.

Add: 6F No.2 Building,
351 Changhe Road
BinJiang Area
Hangzhou 310052 P.R.China

T: (86)571-8577 1352
F: (86)571-8577 1353
www.flavictools.com

Welcome to Flavic Tools & Equipment INC.
We are providing worldwide with the broadest selection of Hand Tools, Power Tools, Air Tools and everything related to Tools and Equipment. As one of the leading companies in China of sourcing, developing, manufacturing, and packing, we have the confidence to fit your needs no matter what you want about tools and equipment.

Since we've founded, we are doing our best to provide our customers with the lowest possible prices, friendly and extremely knowledgeable customer service, and a very diverse kind of products.

CHAMPION brand has been used since 2003. And we have achieved great success with this brand in the past years.

Aiming at providing customers with a basket of high quality tools, we have developed a top quality level of products under our new brand, **FLAVIC** which combines the **FLAV** emanates

from Yellow in Latin and **VIC** emanates from Conquer, symbolizes our confidence to achieve the best Tools and Equipment trading company in China.

Our company is located in Top Sun Science and Technology Park, in the beautiful City Hangzhou with our own warehouse, where thousands of products are on display. For guaranteeing the quality of our products, we setup a factory for professionally testing, assembling, and packing.

President, Guo'An

Guo'An

E: guoan@flavictools.com
M: (86)139-5802-0160

Flavic Tools & Equipment Inc.

Add: 6F No.2 Building,
351 Changhe Road
BinJiang Area
Hangzhou 310052 P.R.China

T: (86)571-8577 1352
F: (86)571-8577 1353
www.flavictools.com



Polisher	Page 1-4
Grinder&Buffer	Page 4-7
Sander	Page 8-9
Saws	Page 9-11
Drills&Fasteners Tools	Page 11-28
Shears&Nibblers&Scissors	Page 28
Cut Off Tools	Page 28-29
Rotary Tools	Page 29-30
Oscillating Tools	Page 30
Wood Working Tools	Page 30-31
Concrete&Masonry Tools	Page 31-34
Lawn&Garden Tools	Page 35-39
Pipe&Cable Tools	Page 39-40
Generators&Engines	Page 40-43
Pumps	Page 43-44
Industrial Fans	Page 44-46
Kits&sets	Page 46
Accessories	Page 46
Others	Page 46-52

P01A025
6"(150mm) Electric Polisher
100V 60W

- Rated Voltage/Frequency: 100V / 50-60HZ
- No Load Speed: 900-3000/min
- Sanding surface size:φ150mm
- Rated Input Power:60W
- Buff pad 2pcs,Sspone pad 1pcs, Towel pad 3pcs
- PSE Certificated



P01A115
6"(150mm) Car Polisher 48W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:3500rpm
- Rated Input Power:48W
- Pad diameter:6" (150mm)
- 1.83M cord
- 2pcs bonnets
- CETLus/GS approved



P01A117
6"(150mm) Car Polisher 48W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:3500rpm
- Rated Input Power:48W
- Pad diameter:6" (150mm)
- 1.83M cord
- 2pcs bonnets
- CETLus/GS approved



P01A123
6"(150mm) Car Polisher 48W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:3500rpm
- Rated Input Power:48W
- Pad diameter:6" (150mm)
- 1.83M cord
- 2pcs bonnets
- CETLus/GS approved



P01A145
6"(150mm) Car Polisher DC 12V 48W

- Rated Voltage/Frequency: DC 12V
- No load rotate speed:3500rpm
- Rated Input Power:48W
- Pad diameter:6" (150mm)
- 3.3M cord
- 2pcs bonnets
- CETLus/GS approved



P01A225B
7"(180mm) Cordless Car Polisher
12V NI-CD 1300mAh

- 12V Ni-CD 1300mAh
- No load rotate speed:2000rpm
- Pad diameter:7" (180mm)
- Charging timer:3~5 hours
- 2pcs bonnet



P01A275D
7"(180mm) Car Polisher DC
12V 25W

- Rate Input voltage:DC 12V
- Noload rotate speed:2550rpm
- Pad diameter:7" (180mm)
- 2pcs bonnets
- Cable effective length:3.8m
- CETLus/GS approved



P01A323
8" Random Orbit Polisher 90W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:3500rpm
- Rated Input Power:90W
- Pad diameter:8" (200mm)
- 1.83M cord
- 2pcs bonnets
- CETLus/GS approved



P01A327
8" Random Orbit Polisher 90W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:3500rpm
- Rated Input Power:90W
- Pad diameter:8" (200mm)
- 1.83M cord
- 2pcs bonnets
- CETLus/GS approved



P01A333
9" Random Orbit Polisher 90W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:3200rpm
- Rated Input Power:90W
- Pad diameter:9" (225mm)
- 1.83M cord
- 2pcs bonnets
- CETLus/GS approved



P01B035B
3"(75mm) Cordless Polisher 12V
Li-ion 1500mAh

- Battery: 12V 1500mAh Li-ion
- No Load Speed: 2600rpm
- Pad diameter:3" (75mm)
- Charging timer:3~5 hours
- 2 x 3" backing pads,240, 320 and 600 grit sand papers, wool bonnet, velcro, foam compounding pad
- CETLus Charger/GS approved



P01B153B
8"(200mm) Cordless Polisher
12V Ni-CD 1300mAh

- 12V Ni-CD 1300mAh
- No load rotate speed:3300rpm
- Pad diameter:8"(200mm)
- Charging timer:3~5 hours
- 2pcs bonnet



P01A523
10"(250mm) Random Orbit Polisher
120W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No-load Speed: 3200rpm
- Rated Input Power:120W
- Pad diameter:10" (250mm)
- 1.83M cord
- 2pcs bonnets
- CETLus/GS approved



P01B065B
4" Cordless Polisher 12V
1300mAh NI-CD

- 12V Ni-CD 1300mAh
- No load rotate speed:2900rpm
- Pad diameter:6"(100mm)
- Charging timer:3~5 hours
- 2pcs bonnet



P01B165B
8" (200mm) Cordless Polisher
18V Ni-CD

- 18V Ni-CD 1300mAh
- No load rotate speed:3300rpm
- Pad diameter:8"(200mm)
- Charging timer:3~5 hours
- 2pcs bonnet



P01A533
10" Random Orbit Polisher 90W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:3200rpm
- Rated Input Power:90W
- Pad diameter:10" (250mm)
- 1.83M cord
- 2pcs bonnets
- CETLus/GS approved



P01B133B
6"(150mm)Cordless Polisher
12V Ni-CD 1300mAh

- 12V Ni-CD 1300mAh
- No load rotate speed:3300rpm
- Pad diameter:6"(150mm)
- Charging timer:3~5 hours
- 2pcs bonnet



P01B233B
6" (150mm) Cordless Polisher
14.4V Li-ion 1300mAh

- 14.4V Li-ion 1300mAh
- No load rotate speed:2600rpm
- Pad diameter:6" (150mm)
- Charging timer:1.5hours
- 2pcs bonnet



P01B235 6"(150mm)Variable Speed Polisher 680W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:2000-6400rpm
- Rated Input Power:680W
- Pad diameter:6" (150mm)
- 1.83M cord
- 1 pc sponge pad
- CETLus/GS approved



P01B313 4" Dual Head Random Orbit Polisher 350W

- Voltage/Frequency: 120V-60Hz/230V-50HZ
- Motor/input power: 350W
- No-load speed:1600-3500r/min
- Ø backing pad: 4" *2
- CETLus
- CE/GS/EMC/ROHSPSE Cable
- Balanced High Performance Professional 4" Dual Polishing Head Variable Speed Random Orbit Dual-Action Polisher



P01B333 6"(150mm)Variable Speed Polisher 900W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:600-3000rpm
- Rated Input Power:900W
- Pad diameter:6" (150mm)
- 1.83M cord
- 1 pc sponge pad
- CETLus/GS approved



P01B353 7"(180mm)Variable Speed Polisher 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:600-3000rpm
- Rated Input Power:1200W
- Pad diameter:7" (180mm)
- 1.83M cord
- 1 pc sponge pad
- CETLus/GS approved



P01B361 7"(180mm)Variable Speed Polisher 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:600-3000rpm
- Rated Input Power:1200W
- Pad diameter:7" (180mm)
- 1.83M cord
- 1 pc sponge pad
- UL Cable/GS approved



P01B362 7"(180mm)Variable Speed Polisher 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:500-3000rpm
- Rated Input Power:1200W
- Pad diameter:7" (180mm)
- 1.83M cord
- 1 pc sponge pad
- UL Cable/GS approved



P01B363 7"(180mm)Variable Speed Polisher 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:600-3000rpm
- Rated Input Power:1200W
- Pad diameter:7" (180mm)
- 1.83M cord
- 1 pc sponge pad
- UL Cable/GS approved



P01B365 7"(180mm)Variable Speed Polisher 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:600-3000rpm
- Rated Input Power:1200W
- Pad diameter:7" (180mm)
- 1.83M cord
- 1 pc sponge pad
- UL Cable/GS approved



P01B367 7"(180mm)Variable Speed Polisher 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:500-3000rpm
- Rated Input Power:1200W
- Pad diameter:7" (180mm)
- 1.83M cord
- 1 pc sponge pad
- UL Cable/GS approved



P01B453 7"(180MM) Polisher 100V 1200W

- With soft-start and equality rotate speed, easy to replace the carbon brush, easily removes swirl marks and scratches, and improves paint gloss.
- 100V~/60Hz,1200W.
- 800-2400RPM.
- Diameter of wheel:180mm.
- Diameter of hole:22mm.
- Spindle diameter:14mm.
- VDE Plug, PSE approved



P03A017 Angle Grinder 100mm 550W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 550W
- Disc diameter: 100mm
- No load speed: 9000rpm
- CETLus/CE approved



P03A021 Angle Grinder 100MM 710W

- Disc diameter: 100mm
- Rated Voltage/Frequency: 120V/60Hz
- Rated Input Power: 710W
- No load speed: 11000rpm
- UL Cable/CE approved



P01B837 7"(180mm) Variable Speed Polisher 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load rotate speed:200-3350RPM
- Rated Input Power:1200W
- Pad diameter:7" (180mm)
- 1.83M cord
- 1 pc sponge pad
- CETLus/GS approved



P03A018 Angle Grinder 115mm 650W

- Disc diameter: 115mm (4-1/2")
- Rated Voltage/Frequency: 120V-60Hz/230V-50HZ
- Rated Input Power: 650W
- No load speed: 11000rpm
- CETLus Certificated
- GS Certificated



P03A025 Angle Grinder 100MM 780W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Disc diameter: 100mm
- Rated Input Power: 780W
- No load speed: 11000rpm
- UL Cable/CE approved



P03A015 Angle Grinder 115mm 580W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 580W
- Disc diameter: 115mm
- No load speed: No load speed: 12000rpm
- CETLus/CE approved



P03A020 Angle Grinder 115mm 700W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 700W
- Disc diameter: 115mm
- No load speed: No load speed: 11000rpm
- CETLus/GS approved



P03A069 Angle Grinder 115mm 800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 800W
- Disc diameter: 115mm
- No load speed: No load speed: 11000rpm
- CETLus/GS approved



P03A123B
Cordless Angle Grinder 115mm
24V Ni-cd 1500mAh

- 24V Ni-cd 1500mAh
- No-Load speed: 7000rpm
- Disc diameter: 115mm
- 1 Hour Fast Charger
- Battery: 1500mAH Ni-cd



P03A127B
Cordless Angle Grinder 115mm
24V Ni-cd 1500mAh

- 20V Ni-cd 1500mAh
- No-Load speed: 7000rpm
- Disc diameter: 115mm
- 1 Hour Fast Charger
- Battery: 2000mAH Ni-cd



P03A157
Cordless Angle Grinder 115mm
14.4 Li-ion 1500mAh

- 14.4V Li-ion 1500mAh
- No-Load speed: 9000rpm
- Disc diameter: 115mm
- 1 Hour Fast Charger
- Battery: 1500mAH Li-ion



P03A163B
Cordless Angle Grinder 115mm
18V Li-ion

- 18V Li-ion 1500mAh
- No-Load speed: 9000rpm
- Disc diameter: 115mm
- 1 Hour Fast Charger
- Battery: 1500mAH Li-ion
- CE/GS approved



P03A173B
Cordless Angle Grinder 115mm
20V Li-ion

- 20V Li-ion 1500mAh
- No-Load speed: 10000rpm
- Disc diameter: 115mm
- 1 Hour Fast Charger
- Battery: 3000mAH Li-ion
- CE/GS approved



P03A215
Angle Grinder 115mm 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Disc diameter: 115mm
- Rated Input Power: 500W
- No load speed: 11000rpm
- UL Cable/CE approved



P03A217
Angle Grinder 115mm 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 500W
- Disc diameter: 115mm
- No load speed: No load speed: 12000rpm
- CETLus/GS approved



P03A225
Angle Grinder 115mm 600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 600W
- Disc diameter: 115mm
- No load speed: No load speed: 12000rpm
- CETLus/GS approved



P03A231
Angle Grinder 115mm 720W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 720W
- Disc diameter: 115mm
- No load speed: No load speed: 11000rpm
- CETLus/GS approved



P03A233
Angle Grinder 115mm 720W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 710W
- Disc diameter: 115mm
- No load speed: No load speed: 10500rpm
- UL Cable/CE approved



P03A243
Angle Grinder 115/125mm 950W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 950W
- Disc diameter: 115/125mm
- No load speed: No load speed: 12000rpm
- CETLus/GS approved



P03A763
Angle Grinder 180mm 1800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 1800W
- Disc diameter: 180mm
- No load speed: No load speed: 12000rpm
- UL Cable/CE approved



P03A237
Angle Grinder 115mm 850W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 850W
- Disc diameter: 115mm
- No load speed: No load speed: 11000rpm
- CETLus/GS approved



P03A245
Angle Grinder 115/125mm 950W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 950W
- Disc diameter: 115/125mm
- No load speed: No load speed: 12000rpm
- CETLus/GS approved



P03C135
Die Grider 300W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 300W
- No load Speed: 500-20000rpm
- Max Diameter: 6mm
- ce approved



P03A239
Angle Grinder 115mm 900W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 900W
- Disc diameter: 115mm
- No load speed: No load speed: 11000rpm
- CETLus/GS approved



P03C435B
1/4" Angle Die Grinder
12V Li-ion

- Rated Voltage: DC 12V
- Rated Voltage: DC 12V
- No Load Speed: 0-16,000rpm
- Collet Size: 1/4"
- 1.5 Hour Fast Charger
- Battery: 2000mAH Li-ion
- CE/GS approvedRated Voltage: DC 12V
- No Load Speed: 0-16,000rpm
- Collet Size: 1/4"
- 1.5 Hour Fast Charger
- Battery: 2000mAH Li-ion
- CE/GS approvedNo Load Speed: 0-16,000rpm
- Collet Size: 1/4"
- 1.5 Hour Fast Charger
- Battery: 2000mAH Li-ion
- CE/GS approved



P03E125 6" Bench Grinder 1/2HP

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power:1/2HP
- No load Speed:3560rpm/min
- Wheel Size: ϕ 150×20×12.7mm
- CETLus/GS approved



P03E135 8" Bench Grinder 3/4HP

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power:3/4HP
- No load Speed:3560rpm/min
- Wheel Size: ϕ 200×20×16mm
- CETLus/GS approved



P03E215 3" Mini Bench Grinder With Flexible Shaft

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power:120W
- No load Speed:1000-9900rpm/min
- Wheel Size: ϕ 75 x 20 x 10mm
- CE/GS approved



P03H021 8"Bench Grinder Buffer

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power:1HP
- No load Speed: 3450rpm/min
- CE/GS approved



P03I135 Shaft Grinder 150W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power:150W
- No load Speed:500-20000RPM
- Max Diameter: 6mm
- CE approved



P03X123 23pcs Angle Grinder Tool Set 600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Disc diameter: 115mm
- Rated Input Power: 600W
- No load speed: 11000rpm
- UL Cable/CE approved



P03Y011 Bench Grinder Stand

- Capacity: 50Ton/25Ton/10Ton
- Working Pressure:0.8-1.2Mpa
- Minimum height: 160mm
- Lifting height: 50Ton:62mm/25Ton: 61mm/10Ton:69mm
- Extension height:75mm+45mm
- N.W.(kg):61



P03Y035 Bech Grinder Stand With Cooling Tary

- Base:cast iron
- Base size:27.8cmX25.5cmX7mm
- Flume size:19cmX10cmX9cmX5mm
- Stand:A3 steel tube
- Stand dia size:74mm
- Stand length:73.3cm



P03Y113 Adjustable pin wrench

- Easy twist knob adjustment. Fits grinder hubs from 3/8" - 1-1/16"
- In size. Over all size: 7-1/2" Cushioned grip



P05A180 Flat Sanders 180W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No-load Speed:12000 OPM
- Rated Input Power:180W
- 1.83M cable
- CETLus/GS approved



P05D100 Mouse Sanders 100W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No-load Speed:10000 OPM
- Rated Input Power:100W
- 1.83M cable
- CETLus/GS approved



P05F235 Belt Sander 300W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 300W
- No-load speed: 2950rpm
- Belt Size: 25.4×760mm
- Disc Size: ϕ 127
- Belt Table Size: 125×125mm
- Disc Table Size: 178×126mm
- Table Tilting Range 0°-45°
- GS/CSA approved



P05B237 Orbital Sander 450W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No-load Speed:12000 OPM
- Rated Input Power:180W
- 1.83M cable
- CE/GS approved



P05D315B 18V Cordless Sander Li-ion

- 18V Li-ion 1500mAh
- No-load speed: 10000 rpm
- Charging Time: 1 hours
- Switch: Forward/Reverse
- Sanding Pad: 140*140*100 mm
- LED Battery indicator
- Soft grip overmold with TPR
- CE/GS approved



P05G811 Cordless Mini Grinder

- Voltage: DC12V
- 6 HSS drills, 2 Mandrels for mounting tools, 3 Polishing wheels ,
- 4 Grinding wheels,1 Metal brush, 16 Cutting wheels,5 Collets,
- 2 Plastic brushes,3 Milling bits, 2 Engraving bits, 5 Grinding bits,
- 1 Combination tool



P05B240 Round Sanders 240W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No-load Speed:13000 OPM
- Rated Input Power:240W
- 1.83M cable
- CETLus/GS approved



P05F125 Belt Sander 250W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 250W
- No-load speed; 3450rpm
- Table Size: 125×125mm
- Belt Size:25.4×760mm
- Table Tilting Range 0°-45°
- GS/CSA approved



P05H155 Disc Sander 550W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 550W
- No-load speed: 3450rpm
- Belt Size: 10"(250mm)
- Table Size: 290×140mm
- Table Tilting Range 0°-45°
- GS/CSA approved



P05I035 Belt & Disc Sander 350W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Disc max. speed: 1819 RPM
- Belt max. speed: 1185 FPM
- Belt Size 4"x36"
- Disc Size ϕ 6"
- Table Size 7"x5"
- Table Tilting Range 0°-45°
- Belt Tilting Range 0°-90°
- GS/CSA approved



P05Z015 Scouring Machine

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Input power:1500W.
- No load speed:1:2500-4500(min)
- Number of gears: 1 speed
- Diameter:140mm
- Change carbon brush easily
- Removing tool easily,Soft start
- Carbide blade
- Variable speed control-6 positions
- GS/CE approved



P07A145 Variable Speed Band Saw 900W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No-load Speed: 0-420FPM
- Blade Size: 44-7/8" x1/2"
- Product dimension: 20x12.5x9 inch
- Include: Carbon brush, band saw blade
- Rated Input Power: 900W
- CETLus/GS approved



P07A235 Portable Metal BandSaw 400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power 400W.
- Speed change: Variable.
- Motor speed: 2000 - 4200RPM
- Swivel range machine head: 0 - 60°.
- Saw band dimensions: 1435 x 0.65 x 12.7 mm.
- Blade speed: 38-80 m/min
- CETLus/GS approved



P07C125 Miter Saw (8" 210mm) 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input Power: 1200W
- No-load Speed: 5000r/min
- 8" single bevel compound
- With laser
- CETLus/GS approved



P07C245 Miter Saw (8"210mm) 1500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1500W
- No-load speed: 5000RPM
- Blade size: 210mm x 24T
- Single bevel,with laser
- CETLus/GS approved



P07C315 Miter Saw (10" 255mm) 1500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input Power: 1500W
- No-load Speed: 4200r/min
- 10" single bevel compound
- With laser
- CETLus/GS approved



P07C325 Miter Saw (10" 255mm) 1500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input Power: 1500W
- No-load Speed: 5000r/min
- 10" single bevel compound
- CETLus/GS approved



P07C335 Miter Saw (10" 255mm) 1600W

- Blade Diameter: 254x15.8x3mm 24T (With blade)
- Rated input Power: 1500W
- No-load Speed: 6000r/min
- 10" single bevel compound
- CETLus/GS approved



P07C355 Miter Saw(10"255mm) 1800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input Power: 1800W
- No-load Speed: 4600r/min
- 10" single bevel compound
- CETLus/GS approved



P07C535 Miter Saw (12" 305mm) 1800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input Power: 1800W
- No-load Speed: 4600r/min
- 12" single bevel compound
- With laser
- CETLus/GS approved



P07D245 Tile Cutter 450W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 450W
- Motor No-load speed: 3000min
- Outer Diameter: 180mm
- Bore: 22.2mm
- Depth of Cut: 34mm
- Table Size: 385x395mm
- Table Tilting Range 0-45 degree
- GS/CSA approved



P07F135 Reciprocating Saws 900W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 900W
- Choke Length: 20mm
- No load Speed:0-2900SPM
- Handle rotates 180° with five positive stops
- CETLus/GS approved



P07F235 Reciprocating Saws 900W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 900W
- Choke Length: 20mm
- No load Speed:0-2800SPM
- Handle rotates 180° with five positive stops
- CETLus/GS approved



P07F439B Cordless Reciprocating Saw 18V Ni-Cd 1200mAh

- 18V Ni-Cd 1200mAh
- No-load Speed:0~2800spm
- Charger:3-5 hrs
- Blade Stroke:7/8"(22mm)
- Max cutting size:95mm
- 2 Saw Blades :Wood +Steel
- CE/GS approved



P07G137 10" Table Saw 1800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1800W
- No-load speed: 5000RPM
- Blade size: 10" x ϕ 5/8"x24T (254mm x 16mm)
- Blade bevel range: 0°-45°
- Cutting Height: 0°max: 85mm 45°max: 65mm
- CETLus/GS approved



P07G145 10" Table Saw 1800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1800W
- No-load speed: 5000RPM+/- 10%,
- Blade size: 10" x ϕ 5/8"(254mm x 16mm)"
- Blade bevel range: 0°-45°
- Miter range: -45° /45°
- Max Cutting Capacity: Cross cut at 90°---3"" (76mm) Bevel cut at 45°---2-1/2"(64mm)
- CETLus/GS approved



P07G237 10" Table Saw 1800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1800W
- No-load speed: 5000RPM
- Blade size: 10" x ϕ 5/8"x24T (254mm x 16mm)
- Blade bevel range: 0°-45°
- Cutting Height: 0°max: 85mm 45°max: 65mm
- CETLus/GS approved



FLAVIC

www. avictools.com

P07J035
147mm Electric Circular Saw 100V 550W

- Rated Voltage/Frequency: 100V-50/60Hz
- Rated Power: 550W
- No Load Speed: 3700/min
- Saw Blade Diameter: 147mm
- Max Cutting Depth: 90° 48mm;45°31mm
- Steel base , Guide ruler
- PSE Certificated



P07J135
6" Circular Saw 1100W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Pat size: 160mm
- Power: 1100W
- No Load Speed: 4600rpm
- Cutting Depth (45°): 38mm
- Cutting Depth (90°): 55mm
- GS approved



P07J235
6" Circular Saw 230V 1100W

- Pat size: 160mm
- Power: 1100W
- No Load Speed: 4600rpm
- Cutting Depth (45°): 38mm
- Cutting Depth (90°): 55mm
- Voltage: 230V-50HZ
- CE Certificated



P07J335
7" Circular Saw 1300W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Pat size: 185mm
- Power: 1300W
- No Load Speed: 4700rpm
- Cutting Depth (45°): 44mm
- Cutting Depth (90°): 65mm
- GS approved



P07J535
8" Circular Saw 1800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Pat size: 200mm
- Power: 1800W
- No Load Speed: 6000rpm
- Cutting Depth (45°): 45mm
- Cutting Depth (90°): 65mm
- GS approved



P07K135B
18V 1* 1500mAh Li-ion Cordless Circular Saw

- Rechargeable battery: 18V/1*1500mAh Li-ion
- No-load speed: 2800 rpm
- Charge time: 1 hours fast charger
- Blade size: 3-3/8"(85mm)
- CETLus Charger/GS approved



P09A123B
3/8"14.4V 1500mAh Ni-Cd Cordless Impact Wrench

- 14.4V Ni-Cd 1500mAh
- 1 hour fast charger
- No-load speed: 0-2400rpm
- Rated impact rate:0-3000bpm
- Max torque: 145 Nm
- 3/8" Square Drive
- Switch: forward & reverse



P09A127B
3/8"14.4V 1700mAh Ni-Cd Cordless Impact Wrench

- 14.4V Ni-Cd 1700mAh
- 1 hour fast charger
- Impact:0-2900/min
- Speed:0-2200/min
- Max.tightening torque:200N.m
- 3/8" Square Drive



P09A313B
1/2" 12V 1700mAh Ni-Cd Cordless Impact Wrench

- 12V Ni-Cd 1700mAh
- 1 hour fast charger
- Impact:0-2900/min
- Speed:0-2200/min
- Max.tightening torque:150N.m
- 1/2" Square Drive



P09A323 1/2" 14.4V 1500mAh NI-CD Cordless Impact Wrench

- 14.4V Ni-Cd 1500mAh
- 1 hour fast charger
- No-load speed: 0-2400/min
- Rated impact rate:0-3000bpm
- Max.tightening torque:180N.m
- 1/2" Square Drive



P09A353B 1/2" 24V 1700mAh Ni-Cd Cordless Impact Wrench

- 24V Ni-Cd 1700mAh
- 1 hour fast charger
- No-load speed: 0-2000/min
- Rated impact rate:0-2600bpm
- Max.tightening torque:350N.m
- 1/2" Square Drive



P09A423B 1/2"18V 1300mAh Li-ion Cordless Impact Wrench

- 18V Li-ion 1300mAh
- 1 hour fast charger
- No-load speed: 0-2200/min
- Rated impact rate:0-2600bpm
- Max.tightening torque:300N.m
- 1/2" Square Drive
- CETLus Charger/GS approved



P09A333B 1/2" 18V 1200mAh Ni-Cd Cordless Impact Wrench

- 18V Ni-Cd 1200mAh
- 1 hour fast charger
- No-load speed: 0-2800/min
- Rated impact rate:0-3000bpm
- Max.tightening torque:150N.m
- 1/2" Square Drive



P09A373B 1/2" 24V 1500mAh Ni-cd Cordless Impact Wrench

- 24V Ni-Cd 1500mAh
- 1 hour fast charger
- No-load speed: 0-2200/min
- Rated impact rate:0-2800bpm
- Max.tightening torque:380N.m
- 1/2" Square Drive



P09A425B 1/2" 18V 1500mAh Li-ion Cordless Impact Wrench

- 18V Li-ion 1500mAh
- 1 hour fast charger
- No-load speed:0-2400/min
- Rated impact rate:0-2800bpm
- Max.tightening torque:200N.m
- 1/2" Square Drive
- CETLus Charger/GS approved



P09A335 1/2" 18V 1500mAh NI-CD Cordless Impact Wrench

- Rechargeable battery: 18V/1*1500mAh NI-CD
- No-load speed: 0-2400/min
- Rated impact rate:0-3000bpm
- Charge time: 1 hour.BS
- Max Torque: 200Nm
- Switch:Forward/Reverse
- Chuck: 1/2" impact wrench chuck
- LED working light • GS certificated



P09A415B 1/2" 14.4V 1500mAh Li-ion Cordless Impact Wrench

- 14.4V Li-ion 1500mAh
- 1 hour fast charger
- No-load speed: 0-2400/min
- Rated impact rate:0-3000bpm
- Max.tightening torque:180N.m
- 1/2" Square Drive
- CETLus Charger/GS approved



P09A429B 1/2" 18V 3000mAh Li-ion Cordless Impact Wrench

- 18V Li-ion 3000mAh
- 1.5 hour fast charger
- No-load speed:0-2000/min
- Rated impact rate:0-2600bpm
- Max.tightening torque:450N.m
- 1/2" Square Drive
- CETLus Charger/GS approved



P09A436B
1/2" 18V 1500mAh Li-ion
Brushless Cordless Impact Wrench

- 18V Li-ion 1500mAh
- 1 hour fast charger
- No-load speed:0-2600/min
- Rated impact rate:0-3000bpm
- Max.tightening torque:260N.m
- 1/2" Square Drive
- Brushless Motor
- CETLus Charger/GS approved



P09A466B
1/2" 20V 3000mAh Li-ion Brushless
Cordless Impact Wrench

- 20V Li-ion 3000mAh
- 1 hour fast charger
- No-load speed:0-2300/min
- Rated impact rate:0-3200bpm
- Max.tightening torque:280N.m
- 1/2" Square Drive
- Brushless Motor
- CETLus Charger/GS approved



P09A525B
1/2"Electric impact Wrench 960W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:960W
- No Load Speed:2700rpm
- Max Torque: 400Nm
- CETLus/GS approved



P09A443B
1/2" 18V 2*3000mAh Impact
Wrench Cordless

- 18V Li-ion 3000mAh
- 1.5 hour fast charger
- No-load speed:0-2600/min
- Rated impact rate:0-2800bpm
- Max.tightening torque:600N.m
- 1/2" Square Drive
- CETLus Charger/GS approved



P09A473B
1/2" 24V 1300mAh Li-ion Cordless
Impact Wrench

- 24V Li-ion 1300mAh
- 1 hour fast charger
- No-load speed: 0-2200/min
- Rated impact rate:0-2600bpm
- Max.tightening torque:300N.m
- 1/2" Square Drive
- CETLus Charger/GS approved



P09A565
1/2" Electric Impact Wrench 450W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:450W
- No Load Speed:2200rpm
- Max Torque: 320Nm
- GS approved



P09A453B
1/2" 20V 3000mAh Li-ion Impact
Wrench Cordless

- 20V Li-ion 3000mAh
- 1.5 hour fast charger
- No-load speed:0-2400/min
- Rated impact rate:0-3200bpm
- Max.tightening torque:250N.m
- 1/2" Square Drive
- CETLus Charger/GS approved



P09A521
1/2" Electric Impact Wrench 900W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:900W
- No Load Speed:2200rpm
- Max Torque: 300Nm
- GS approved



P09A567
1/2" Electric Impact Wrench 600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:600W
- No Load Speed:1900rpm
- Max Torque: 350Nm
- GS approved



P09A575B
1/2" Electric Impact Wrench
1100W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:2200W
- No Load Speed:1900rpm
- Max Torque: 450Nm
- GS approved



P09A625D
1/2 DC Impact Wrench 170W

- Voltage: DC 12V
- Power:170W
- Max Torque: 300Nm
- Shaft size:1/2"
- CE approved



P09A875
1" Electric Impact Wrench
1050W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:1050W
- No Load Speed:4100rpm
- Max Torque: 820Nm
- CE approved



P09A613D
1/2 DC Impact Wrench 95W

- Voltage: DC 12V
- Power:95W
- Max Torque: 350Nm
- Shaft size:1/2"
- CE approved



P09A635D
1/2" DC Impact Wrench 180W

- Voltage: DC 12V
- Power:180W
- Max Torque: 380Nm
- Shaft size:1/2"
- CE approved



P09C075B
1/4" Cordless Ratchet Wrench
7.2V 1300mAh Lithium

- Voltage: DC 7.2V 1300mAh Lithium
- Max torque: 8N.M
- No Load Speed: 200rpm
- Shaft size:1/4"
- 3-5hours charger
- GS certificated



P09A617D
1/2 DC Impact Wrench 100W

- Voltage: DC 12V
- Power:100W
- Max Torque: 350Nm
- Shaft size:1/2"
- CE approved



P09A773
3/4" Electric Impact Wrench
600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:600W
- No Load Speed:1900rpm
- Max Torque: 500Nm
- CE approved



P09C273B
3/8" Cordless Ratchet Wrench
7.2V 1300mAh Lithium

- Voltage: DC 7.2V 1300mAh Lithium
- Max torque: 8N.M
- No Load Speed: 200rpm
- Shaft size:3/8"
- 3-5hours charger
- GS certificated



P09C435B 1/2" Cordless Ratchet Wrench 14.4V 1*1700mAh NI-CD

- Voltage: DC 14.4V 1*1700mAh NI-CD
- Max torque: 75N.M
- No Load Speed: 200rpm
- Shaft size: 1/2"
- 1 hour charge



P09E009B 1/8"18PC Cordless Precision Screwdriver Set

- 3V Precision Screwdriver
- 1/8" bit driver
- 2PC AAA NI-CD battery included
- With 18pc chrome plated 50Cr-V screwdriver bits (PH000,PH00,PH0,
- PH1 ;SL1,SL1.5,SL2,SL2.5;T3,T4,T5,T6,T7, T8;PZ00,PZ00,PZ0,PZ1)
- Built-in LED work light with independent on/off switch
- 120RPM • GS certificated



P09E127B Cordless Screwdriver Set 3.6V Li-Ion 1300mAh

- Voltage: 3.6V DC.
- Battery: Li-Ion, 1300mAh.
- No load speed: 150 rpm.
- Max Torque: 2.5 Nm.
- Keyless Chuck: 1/4" (Ø 6.35mm).
- Charging time: 3-5 hours.
- LED Work light.
- Switch: forward & reverse.
- 100pcs 25mm screwdriver bits.
- 1pcs 50mm adaptor bit holder.
- 1pcs 60mm magnetic bit holder
- GS/UL charger



P09E007B 1/8"13PC Cordless Precision Screwdriver Set

- 3V dry battery screwdriver
- 1/8" bit driver
- 2PC AAA NI-CD Battery
- With 13pc bits chrome plated 50Cr-V screwdriver bits (PH000,PH00,
- PH0,PH1;SL1,SL1.5,SL2,SL2.5; T3,T4,T5,T6,T7)
- Built-in LED work light with independent on/off switch
- Has a quick-change chuck
- 120RPM • GS certificated



P09E115B 3.6V Cordless Screwdriver Li-ion 1*1300mAh

- Voltage: 3.6V Li-ion 1*1300mAh
- No-load speed: 180 rpm
- Charging Time: 3-5 hours
- Switch: Forward/Reverse
- Chuck: 1/4"
- Max torque setting: 3Nm
- Lithium-Ion Battery protection
- Soft grip overmold with TPR
- LED working light function and battery indicator
- Accessories: 24pcs bits
- GS certificated



P09E147B Cordless Screwdriver 3.6V Li-Ion 1500mAh

- Voltage: 3.6V
- Battery Type: Lithium-Ion Battery.
- Battery Capacity: 1.5A.
- No-load Speed: 230RPM.
- Max. Torque: 2.6Nm.
- Screw Sizes: 6.35mm (1/4").
- Magazine Capacity: 14 bits
- CE/GS approved



P09E117B 53pcs Folding Screwdriver Set Li-ion 1300mAh

- Power: Li-ion, 1300mAh 3.6V
- No-load speed: 210rpm
- Clutch: 9 setting rings
- Max torque: 4Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 3-5 hours
- Switch: forward & reverse 53pcs accessories: 52pcs 25mm Carbon steel bits: PH1*5, PH2*5, PH3*4; PZ1*4, PZ2*4, PZ3*4, H3*2, H4*2, H5*2, T8*2, T10*2, T15*2, T20*2, T25*2, T40*2 SL3*2, SL4*2, SL5*2, SL6*2 1pc 60mm bits holder
- GS/UL charger



P09E149B 3.6V 1/4" Folding Screwdriver Li-ion 1500mAh

- Power: Li-ion, 1500mAh 3.6V
- No-load speed: 210rpm
- Max torque: 5Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 3-5 hours
- Switch: forward & reverse
- 6bits 25MM: PZ1 PH1 H2 S4 S6 T10 (CRV)
- CE/GS/EMC/RoHS approved



P09E163B 3.6V 1/4" Folding Screwdriver Li-ion 1300mAh

- Power: Li-ion, 1300mAh 3.6V
- No-load speed: 210rpm
- Clutch: 9 setting rings
- Max torque: 3Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 3-5 hours
- Switch: forward & reverse
- CE/GS/EMC/RoHS approved



P09E213B 1/4" Folding Screwdriver 4.8V Ni-Cd 600mAh

- 4.8V with battery capacity
- LED indicator and LED light
- Battery capacity: Ni-Cd 600mAh
- No-load speed: 200 rpm
- Max torque setting: 2.5NM
- Charger: 3-5 hour Charrger
- Chuck capacity: 6.35mm (1/4")
- CE/GS/EMC/RoHS approved



P09E521B 7.2V 1/4" Screwdriver Li-ion 1300mAhmAh

- Power: Li-ion 1300mAh 7.2V
- No-load speed: 230rpm
- Max torque: 10Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 3-5 hours
- CE/GS/EMC/RoHS approved



P09E209B 4.8V 1/4" Folding Screwdriver NI-CD 600mAh

- Batttery capacity: NI-CD 600mAh 4.8V
- No-load speed: 180rpm
- Max torque: 2.5Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 3-5 hours
- Switch: forward & reverse
- CE/GS/EMC/RoHS approved



P09E227B 4.8V Cordless Screwdriver Ni-Cd 1*800mAh

- Voltage: 4.8V DC
- Battery: Ni-Cd, 800mAh
- No load speed: 150 rpm
- Max Torque: 2.5 Nm
- Keyless Chuck: 1/4" (Ø 6.35mm)
- Charging time: 3-5 hours
- Switch: forward & reverse
- CE/GS/EMC/RoHS approved



P09E523B 1/4" 12V 1* 1300mAh Li-ion Cordless Two Speed Screwdriver

- Rechargeable battery: 12V/1*1300mAh Li-ion
- No-load speed: 0-400/0-1400rpm
- Charge time: 1 hours fast charger
- Max Torque: 18 N.m /28N.m
- Switch: Forward/Reverse
- Chuck: 1/4",
- LED working light, Belt hooks
- Clutch: 18+1 setting
- CE/GS/EMC/RoHS approved



P09E211B 4.8V 1/4" Screwdriver Ni-Cd 600mAh

- Power: Ni-Cd 600mAh 4.8V
- No-load speed: 150rpm
- Max torque: 2.5Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 3-5 hours
- CE/GS/EMC/RoHS approved



P09E513B 1/4" 12V Cordless Impact Screwdriver Li-ion 1300mAh

- Power: Li-ion, 1300mAh 12V
- No-load speed: 0-2400 rpm
- Rated Impact: 0-3200 ipm
- Max torque: 70Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 1.5 hours
- Switch: forward & reverse
- CE/GS/EMC/RoHS approved



P09E533B 1/4" 14.4V Cordless Impact Screwdriver Li-ion 1300mAh

- Power: Li-ion, 1300mAh 14.4V
- No-load speed: 0-2400 rpm
- Rated Impact: 0-3200 ipm
- Max torque: 90Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 1.5 hours
- Switch: forward & reverse
- CE/GS/EMC/RoHS approved



P09E535B
1/4" 14.4V Cordless impact
Screwdriver NI-CD 1300mAh

- Power: NI-CD, 1300mAh 14.4V
- No-load speed: 0-2400 rpm
- Rated Impact: 0-3200 ipm
- Max torque: 90Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 3-5 hours
- Switch: forward & reverse



P09E623
1/4" Impact driver 230W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input power: 230W
- Hex shank: 6.35mm(1/4")
- Impacts per minute: 0-3200IPM
- No load speed: 0-3600rpm
- Max. torque: 100N.m
- Switch: forward & reverse
- CE approved



P09F123
Electric Drywall Screwdriver 400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:4.2A/400W
- No-load speed:0-3000r/min
- Cutting depet: wood 25mm steel 10mm
- CETLus/GS approved



P09E553B
1/4"18V Cordless Impact
Screwdriver Li-ion 1300mAh

- Power: Li-ion, 1300mAh 18V
- No-load speed: 0-2400 rpm
- Rated Impact: 0-3200 ipm
- Max torque: 100Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 1.5 hours
- Switch: forward & reverse
- CE/GS/EMC/RoHS approved



P09E723
1/4" Impact driver 450W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input power: 450W
- Hex shank: 6.35mm(1/4")
- Impacts per minute: 0-3000IPM
- No load speed: 0-3200rpm
- Max. torque: 158N.m
- Switch: forward & reverse
- CE/GS approved



P09F223
1/4" Electric Screwdriver 400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power:400W
- No-Load Speed:0-3000rpm
- Six Point Sockets Length:60mm
- CE approved



P09E555B
1/4" 18V Cordless impact
Screwdriver NI-CD 1300mAh

- Power: NI-CD, 1300mAh 18V
- No-load speed: 0-2400 rpm
- Rated Impact: 0-3200 ipm
- Max torque: 90Nm
- Chuck: 1/4" (Ø 6.35mm)
- Charge time: 3-5 hours
- Switch: forward & reverse



P09F023B
Cordless Drywall Screwdriver
18V 4.0Ah

- Power: Li-ion,1*4.0Ah,18V
- Speed:0-2000rpm
- Rated Input Power:350W
- Driver Bit Size:Ø5.5*150mm
- Screw Size:Ø3.5*25-50mm
- CE approved



P09F233
1/4" Electric Screwdriver 450W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power:450W
- No-Load Speed:0-3000rpm
- Six Point Sockets Length:60mm
- CE approved



P09G025
3/8" Electric Drill 100V 25W

- Rated Power: 25W/50-60HZ
- No Load Speed: 170/min
- Torque: 4-36kgf.cm
- Switch: Forward/Reverse
- PSE approved



P09G125
3/8" Electric Drill 23+1 Torque
setting 280W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input power: 280W
- No-load speed: 0-750r / min
- Torque settings: 23+1
- Metal drilling capacity: 10mm,wood: 13mm
- CE approved



P09G137
3/8" Electric Drill 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Amperage:4.2A
- Rated Input Power: 500W
- No load speed: 3000rpm
- Chuck size:10mm, Reversible
- CETLus/GS approved



P09G045
3/8" Electric Drill 100V 70W

- Rated Power: 70W/50-60HZ
- No Load Speed: 0-500/min
- Torque: 0-80kgf.cm
- Switch: Forward/Reverse
- PSE approved



P09G135
3/8" Electric Drill 380W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Amperage:3.2A
- Rated Input Power: 380W
- No load speed: 3000rpm
- Chuck size:10mm
- CETLus/GS approved



P09G138
3/8" Electric Drill 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:4.2A/500W
- No-load speed:0-3000r/min
- Chuck size:10mm
- CETLus/GS approved



P09G123
3/8" Electric Drill 15+1 Torque
setting 280W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated input power: 280W
- No-load speed: 0-750r / min
- Torque settings: 15+1
- Metal drilling capacity: 10mm,wood: 13mm
- CE approved



P09G136
3/8" Electric Drill 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:4.2A/500W
- No-load speed:0-3000r/min
- Chuck size:10mm
- CETLus/GS approved



P09G139
3/8" Electric Drill 380W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 380W
- No load speed: 3000rpm
- Chuck size:10mm, Reversible
- UL charger/GS approved



P09G140 3/8" Electric Drill 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:4.2A/500W
- No-load speed:0-3000r/min
- Chuck size:10mm
- CETLus/GS approved



P09G165 1/2" Electric Drill 720W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Input power: 720W
- Rated Voltage:120-110v
- No load speed:0-2800r/min
- Chuck size:13mm
- CETLus/GS approved



P09G353B 3/8" 19.2V 1000mAh Ni-Cd Cordless Drill Kit

- Rechargeable battery:1000mah Ni-Cd
- No-Load speed 0-550rpm
- Keyless chuck:0.8-10mm
- Charging time 3-5 hours
- Torque setting: 19+1 position
- 13pcs accessories:6pcs drill bits, 6pcs screwdriver bits and one magnetic holder



P09G143 3/8" Electric Drill 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:4.2A/500W
- No-load speed:0-3000r/min
- Chuck size:10mm
- CETLus/GS approved



P09G333B 3/8" 18V 1200mah Ni-Cd Cordless Drill Kit

- Rechargeable battery:1200mah Ni-Cd.
- No-Load Speed 0-550rpm.
- Keyless Chuck:0.8-10mm.
- Charging Time:3-5 hours
- Torque setting: 16 position torque setting.
- Max torque: 12Nm.
- Switch: forward & reverse.
- Motor brake: yes



P09G357B 3/8" 19.2V 1000mAh NI-CD 13pc Drill Kit

- Battery capacity:1000mah NI-CD
- Chuck:10mm(3/8")
- Switch: variable speed with brake
- Charger: 3-5hour Charrger
- No-load speed: 0-550rpm/min
- Torque setting:19+1 positions
- Accessories: 6pcs 25mm bits(PH1,PH2,PZ1, PZ2, S5,S6),6pcs drill bits (1.5,2.5,3,4,5,6) and 1pc magnetic holder(58mm)
- Max torque setting:16-17NM

P09G145 3/8" Electric Drill 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:4.2A/500W
- No-load speed:0-3000r/min
- Chuck size:10mm
- CETLus/GS approved



P09G345B 3/8" 19.2V 1000mAh Ni-Cd Drill Kit

- Rechargeable battery: 1000mah Ni-Cd Pack.
- No-Load Speed 0-550rpm.
- Keyless Chuck:0.8-10mm.
- Charging Time 5-7 hours.
- 230V 50HZ, GS Approved Charger.
- Torque setting: 16+1 position torque setting.
- 13pcs accessories:6pcs drill bits, 6pcs screwdriver bits and one magnetic holder



P09G413B 3/8" 10.8V 1300mAh Li-ion Cordless Drill

- Battery capacity:1300mah NI-CD
- Dia. of Chuck: Ø10mm
- Max Torque: 22Nm
- No Load Speed: 0-350/0-1250 rpm
- Torque Settings: 19+1
- harger Time: 1 hour
- Max. drilling dia: wood: 20mm / steel:6mm



P09G425B 3/8" 14.4V 1300mAh Li-ion Cordless Two Speed Drill

- Rechargeable battery:1300mAh Li-ion
- No-load speed: 0-400/0-1400rpm
- Charge time: 1 hours fast charger
- Max Torque: 32Nm
- Switch:Forward/Reverse
- Chuck: 3/8",
- LED working light,Belt hooks
- Clutch:18+1 setting
- CE/GS approved



P09G415B 3/8" 12V 1300mAh Cordless Drill Li-ion

- Rechargeable battery:1300mAh Li-ion
- 2 gears speed: 0-350rpm/0-1350rpm
- Charging Time: 1hours
- Switch: Forward/Reverse
- Torque Grade: 18+1
- 10mm normal keyless chuck
- Max torque setting: 25Nm
- CE/GS approved



P09G427B 3/8" 14.4V 1300mAh Li-ion Cordless Two Speed Drill

- Rechargeable battery:1300mAh Li-ion
- No-load speed: 0-450/0-1500rpm
- Charge time: 1 hours fast charger
- Max Torque: 32Nm
- Switch:Forward/Reverse
- Chuck: 3/8"
- LED working light,Belt hooks
- Battery with mobile power function
- Clutch:15+1 setting
- CE/GS approved



P09G423B 3/8" 14.4V 1300mAh Li-ion Cordless Drill

- Rechargeable battery:1300mAh Li-ion
- Dia. of Chuck: Ø10mm
- Max Torque: 28Nm
- No Load Speed: 0-350/0-1250 rpm
- Torque Settings: 19+1
- Charger Time: 1 hour
- Max. drilling dia: wood:20mm / steel:6mm
- CE/GS approved



P09G433B 3/8" 18V 1300mAh Li-ion Cordless Drill

- Rechargeable battery:1300mAh Li-ion
- Dia. of Chuck: Ø10mm
- Max Torque: 30Nm
- No Load Speed: 0-350/0-1250 rpm
- Torque Settings: 19+1
- Charger Time: 1 hour
- Max. drilling dia: wood:20mm / steel:6mm
- CE/GS approved



P09G435B
3/8" 18V 1300mAh Li-ion Cordless Drill Kit

- Rechargeable battery:1300mah Li-ion.
- No-Load Speed 0-550rpm.
- Keyless Chuck:0.8-10mm.
- Charging Time:3-5 hours, BS.
- Torque setting: 16 position torque setting.
- 13pcs accessories:6pcs drill bits, 6pcs screwdriver bits and one magnetic holder.
- Max torque: 15Nm
- CE/GS approved



P09G436B
3/8" 18V 1300mAh Li-ion Cordless Two Speed Drill

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Input power:1500W.
- No load speed:l:2500-4500(min)
- Number of gears: 1 speed
- Diameter:140mm
- Change carbon brush easily
- Removing tool easily,Soft start
- Carbide blade
- Variable speed control-6 positions
- GS/CE approved



P09G437B
3/8" 18V 1300mAh Li-ion Cordless Two Speed Drill

- Rechargeable battery:1300mAh Li-ion
- No-load speed: 0-450/0-1500rpm
- Charge time: 1 hours fast charger
- Max Torque: 35Nm
- Switch:Forward/Reverse
- Chuck: 3/8"
- LED working light,Belt hooks
- Battery with mobile power function
- Clutch:15+1 setting
- CE/GS approved



P09G443B
3/8" 18V 1500mAh Li-ion Cordless Drill

- Rechargeable battery:1500mAh Li-ion
- Dia. of Chuck: Ø10mm
- Max Torque: 50Nm
- No Load Speed: 0-400/0-1400 rpm
- Torque Settings: 19+1
- Charger Time: 1 hour
- CE/GS approved



P09G523B
1/2" 14.4V 1300mAh NI-CD Cordless Drill

- Rechargeable battery:1300mAh NI-CD
- No-load speed: 0-350/0-1250 rpm
- Max torque: 23Nm
- Chuck: 1/2"(Ø 13mm)
- Charge time: 3-5 hours
- Switch: forward & reverse,Two Speed



P09G533B
1/2" 18V 1300mAh NI-CD Cordless Drill

- Rechargeable battery:1300mAh NI-CD
- No-load speed: 0-350/0-1250 rpm
- Max torque: 25Nm
- Chuck: 1/2"(Ø 13mm)
- Charge time: 3-5 hours
- Switch: forward & reverse,Two Speed



P09G535B
1/2"18V 1000mAh Ni-Cd Cordless Drill

- Rechargeable battery:1000mah Ni-Cd
- With battery indicator
- Swith: variable speed with brake
- 5hour Charrger
- No-load speed: 0-550 rpm
- Chuck: 13mm(1/2")
- Torque setting: 21+1 positions
- Max torque setting:16-17NM



P09G637B
1/2" 18V 1500mAh Li-ion Brushless Cordless Drill

- Rechargeable battery:1500mAh Li-ion
- 2 speed Switchable: 0-450/0-1600 rpm
- Charging Time:1hours
- Switch:Forward/Reverse
- Torque Grade:19+1
- Quick-changing chuck: 13mm
- Max torque setting: 50Nm
- Brushless Motor
- Lithium-Ion Battery protection
- Soft grip overmold with TPR
- CE/GS approved



P09G623B
1/2" 14.4V 1300mAh Li-ion Cordless Drill

- Rechargeable battery:1300mAh Li-ion
- No-load speed: 0-350/0-1250 rpm
- Max torque: 28Nm
- Chuck: 1/2"(Ø 13mm)
- Charge time: 1.5 hours
- Switch: forward & reverse,Two Speed
- CE/GS approved



P09G665B
1/2" 20V 3000mAh Li-ion Brushless Cordless Drill

- Rechargeable battery:3000mAh Li-ion
- No-load speed: 0-500RPM/0-1700RPM
- No-load speed: 0-500RPM/0-1700RPM
- Max. Torque: 60Nm
- Torque Setting: 18+1
- Chuck: 2-13mm metal chuck with autolock system
- Motor: DC brushless motor
- Charging Time:1 hour
- CE/GS approved



P09G633B
1/2" 18V 1300mAh Li-ion Cordless Drill

- Rechargeable battery:1300mAh Li-ion
- No-load speed: 0-350/0-1250 rpm
- Max torque: 30Nm
- Chuck: 1/2"(Ø 13mm)
- Charge time: 1.5 hours
- Switch: forward & reverse,Two Speed
- CE/GS approved



P09H115
3/8"Angel drill 450W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:4.2A/400W
- No-load speed:0-3000r/min
- Cutting depet: wood 25mm steel 10mm
- CETLus/GS approved



P09I125
1/2" Impact drill 600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:5A/600W
- No-load speed:0-2800r/min
- Chuck size:13mm
- CETLus/GS approved



P09I145
1/2" Impact drill 750W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor/input power:6.3A/750W
- No-load speed:0-2800r/min
- Chuck size:13mm
- CETLus/GS approved



P09I423B
3/8" 12V 1300mAh Li-ion Cordless Two Speed Impact Drill

- Rechargeable battery:1300mAh Li-ion
- No-load speed: 0-400/0-1400rpm
- Charge time: 1 hours fast charger
- Max Torque: 30Nm
- Switch:Forward/Reverse
- Chuck: 3/8",
- LED working light,Belt hooks
- Impact rate: 0~19500 Bpm
- Clutch:18+1 setting
- CE/GS approved



P09I435B
3/8" 18V 1300mAh Li-ion Cordless Two Speed Impact Drill

- Rechargeable battery:1300mAh Li-ion
- No-load speed: 0-450/0-1500rpm
- Charge time: 1 hours fast charger
- Max Torque: 35Nm
- Switch:Forward/Reverse
- Chuck: 3/8",
- LED working light,Belt hooks
- Battery with mobile power function
- Impact rate: 0~19500 Bpm
- Clutch:15+1 setting
- CE/GS approved



P09I525B
1/2" 14.4V 1300mAh NI-CD Cordless impact Drill

- Rechargeable battery:1300mAh NI-CD
- No-load speed: 0-350/0-1250 rpm
- Max torque: 23Nm
- Chuck: 1/2"(∅ 13mm)
- Charge time: 3-5 hours
- Switch: forward & reverse,Two Speed



P09I526B
1/2" 14.4V 1300mAh NI-CD Cordless impact Drill

- Rechargeable battery:1300mAh NI-CD
- No-load speed: 0-400/0-1400 rpm
- Max torque: 25Nm
- Chuck: 1/2"(∅ 13mm)
- Charge time: 3-5 hours
- Switch: forward & reverse,Two Speed



P09I667B
1/2" 20V 3000mAh Li-ion Cordless Hammer Drill

- Rechargeable battery:3000mAh Li-ion
- No-load Speed:0-400RPM and 0-1500RPM
- Impact Rate: 0-6000BPM/0-22500BPM
- Max.Torque: 50Nm
- Torque Setting:16
- 2-13mm all metal chuck
- Automatic spindle lock function
- CE/GS approved



P09I673B
1/2" 20V 3000mAh Li-ion Cordless Compact Drill

- Rechargeable battery:3000mAh Li-ion
- No-load Speed:0-400RPM/0-1500RPM
- Max.Torque: 50Nm
- Torque Setting:16+1
- 2-13mm metal chuck with autolock system
- Automatic spindle lock function
- CE/GS approved



P09I535B
1/2" 18V 1300mAh NI-CD Cordless impact Drill

- Rechargeable battery:1300mAh NI-CD
- No-load speed: 0-350/0-1250 rpm
- Max torque: 25Nm
- Chuck: 1/2"(∅ 13mm)
- Charge time: 3-5 hours
- Switch: forward & reverse,Two Speed



P09I626B
1/2" 14.4V 1500mAh Li-ion Cordless impact Drill

- Rechargeable battery:1500mAh Li-ion
- No-load speed: 0-400/0-1400 rpm
- Max torque: 25Nm
- Chuck: 1/2"(∅ 13mm)
- Charge time: 1.5 hours
- Switch: forward & reverse,Two Speed
- CE/GS approved



P09K130
5 Speed Drill Press 300W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ , Power 300W
- Spindle Speed 5 speed , 760,1150,1630,2180,3070
- Motor No-load Speed 1700rpm
- Chuck B16/1.5-13mm
- Spindle Taper B16
- Max.Drilling Depth 50mm
- CSA/GS approved



P09I536B
1/2" 18V 1300mAh NI-CD Cordless impact Drill

- Rechargeable battery:1300mAh NI-CD
- No-load speed: 0-400/0-1400 rpm
- Max torque: 25Nm
- Chuck: 1/2"(∅ 13mm)
- Charge time: 3-5 hours
- Switch: forward & reverse,Two Speed



P09I635B
1/2" 18V 1500mAh Li-ion Cordless impact Drill

- Rechargeable battery:1500mAh Li-ion
- No-load speed: 0-350/0-1250 rpm
- Max torque: 30Nm
- Chuck: 1/2"(∅ 13mm)
- Charge time: 1.5 hours
- Switch: forward & reverse,Two Speed
- CE/GS approved



P09K135
5 Speed Drill Press 350W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max Drilling Diameter (mm): Φ13mm(1/2")
- Motor Power (W):350W
- Chuck Capacity (mm):1.5-13
- Spindle Travel (mm):50
- Class Of Speed:5 (740-3140R.P.M.)
- CETLus/GS approved



P09I625B
1/2" 14.4V 1500mAh Li-ion Cordless impact Drill

- Rechargeable battery:1500mAh Li-ion
- No-load speed: 0-350/0-1250 rpm
- Max torque: 23Nm
- Chuck: 1/2"(∅ 13mm)
- Charge time: 3-5 hours
- Switch: forward & reverse,Two Speed
- CE/GS approved



P09I636B
1/2" 18V 1500mAh Li-ion Cordless impact Drill

- Rechargeable battery:1500mAh Li-ion
- No-load speed: 0-400/0-1400 rpm
- Max torque: 30Nm
- Chuck: 1/2"(∅ 13mm)
- Charge time: 1.5 hours
- Switch: forward & reverse,Two Speed
- CE/GS approved



P09K145
12 Speed Drill Press 450W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 450W
- Spindle Speed 12 speed
- Motor No-load Speed 1700rpm
- Chuck B16/3-16mm,Spindle Taper B16
- Max.Drilling Depth: 60mm
- CSA/GS approved



P09K149 9 Speed Drill Press 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max Drilling Diameter (mm):Φ16mm(5/8")
- Motor Power (W):500W
- Chuck Capacity (mm):3-16
- Spindle Travel (mm):50
- Class Of Speed:9 (480-3000R.P.M.)
- CETLus/GS approved



P09W011 Heavy Duty Drill Powered Pump

- 650 GPH delivery rate
- Attaches to power drill or electric motor with a coupler
- Water, corrosion, heat and wear resistant
- Fits standard garden hose
- Use with fresh or salt water, solvents, oils, insecticides and fertilizers
- Maximum speed (rpm) 3000 RPM
- Flow rate : 650 GPH
- ABS housing



P09W015 Right Angle Drill Attachment Driver 90°- 1/4" Hex Shanks

- Drive screws in hard-to-reach places
- Magnetic Bit Holder, 1/4" Drive
- Can be used in forward or reverse
- Well built and heavy duty
- Accepts 1/4" Hex shank Driver drill bits



P09K155 16 Speed Drill Press 550W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:550W
- Spindle Speed: 16 speed
- Motor No-load Speed 1700rpm
- Chuck:B16/3-16mm,Spindle Taper: MT2
- Max. Drilling Depth:80mm
- CSA/GS approved



P09W012 Right Angle Drill Attachment Chuck Adapter Electric Power Cordless 3/8 90 Degree

- Attaches to most standard drills.
- Attachment has heavy-duty metal housing, heat-treated steel shank.
- Double heat-treated helical gear (1:1 gear ratio) and close-tolerance.
- Industrial-grade chuck.
- One of a kind unique 90-Degree attachment allows you to drill in tight.
- Corners and awkward angles



P09X023B 30pcs 7.2V 1300mAht Li-ion Cordless Drill Se

- Rechargeable battery:1300mAh Li-ion
- No-Load speed: 0-550r/mi.
- Torque stage: 16+1.
- Keyless chuck: 0.8-10mm.
- Charging time: 3-5hours.
- Electric brake,LED work light,Soft grip.
- 1pc charger,1pc charger stand, 1pc magnetic bit holder,9pcs drills, 14pcs screw bits,1pc holder,1pc plier, 1pc utility knife,1pc Tool bag
- CE/GS approved

P09K235 5 Speed Drill Press 350W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power 350W S2 15min
- Spindle Speed 5 speed (580/850/1220/1650/2650rpm)
- Motor No-load Speed 1450rpm
- Chuck B16/1.5-13mm
- Max.Drling Depth 50mm
- CSA/GS approved



P09W013 Right-Angle Drill Attachment

- Material: Plastic Shell, Zinc Alloy Head
- Contains: 4 Screwdriver Bits
- Side hande put left or right
- 1/4"heat treated carbon steel hex shaft



P09X033B 56pcs 7.2V 1300mAh Li-ion Cordless Drill Set

- Rechargeable battery:1300mAh Li-ion
- No-Load speed: 0-550r/mi.
- Torque stage: 16+1.
- Keyless chuck: 0.8-10mm.
- Charging time: 1hours.
- Electric brake,LED work light,Soft grip.
- 1pc 6"Adjustable Wrench ,1pc 6"Slip Joint Pliers,1pc 6"Long nose Plier,1pc Knife, 1pc Tape Measure,1pc Claw hammer, 1pc ratchet screwdrive,32pcs bits, 10pc drill bit, 4pcs spark socket, 1pc extension,1pc Tool bag
- CE/GS approved



P09X063B 18v Twin Cordless Drill Set

- 18v Twin Cordless Drill Set:1PC Heavy Duty Hammer Drill,1PC Compact Drill Driver,2PC Batteries,1PC Fast Charger & Drill Bit Accessories
- Accessories Included: 5pc HSS Titanium Coated Drill Bits 6mm, 7mm, 8mm, 9mm, 10mm; 4pc Titanium Coated Masonry Drill Bits 8mm, 9mm, 10mm, & 12mm; 3pc Titanium Coated Wood Drill Bits 7mm, 8mm, & 9mm; 3pc Titanium Coated Wood Boring Flat Drill Bits 19mm, 22mm, & 32mm
- Voltage:18V
- Drill Bit Pick Up Size:1.5-10MM
- Clutch:16+1
- No Load Speed : 550/Min
- Torsion:14NM
- Charging time: 3-5hours.



P09X140 40pcs Impact Drill Set 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Input power: 500W
- No-load Speed:0-3000r/min
- Drill Capacity: steel: 10mm / wood :25mm
- Accessories: 1pc side handle, 2pcs 6*75MM screwdriver,1pc AS handle, 1pc 6" combination plier,1pc 6" long nose plier,1pc utility knife,3pc twist drill, 3pc wood working drill,3pc masonry drill, 1pc extension bar, 20pcs 25MM bit, 1pc claw hammer



P09Y011 Diamond Tipped Metal Hole Saw Drill

- Product Name : Glass Hole Saw
- Material :Carbon Steel, Diamond (The Head of Drill Bit)
- Drilling Diameter : 12mm / 1/2", Shank Diameter : 6.5mm / 1/4"
- Total Length : 50.5mm / 2"
- Color : Silver Tone
- Net Weight : 11g



P09Y115 Step Drill 1/4inch - 3/4inch Titanium coated

- Material:HSS4241,Titanium coated
- Drills from1/4 in to 3/4 in (1/4"-5/16"-3/8"-7/16"-1/2"-9/16"-5/8"-11/16"-3/4")

P09X189 89pcs Impact Drill Kits 500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- 1pc13mm Impact Drill
- Input power: 500W
- No-load Speed:0-3000r/min
- Drill Capacity: steel: 10mm / wood :25mm
- Accessories: 22pcs 25MM bit,12pcs 50MM bit,1pc Magnetic bit holder, 9pcs socket, 3pcs wire wheel brush,2pcs wire wheel brush holder,10pcs wood working drill, 10pcs masonry drill,10pcs HSS,3pcs wood working flat bit 5pcs sanding stone, 2pcs counter sink



P09Y113 Step Drill 1/8inch- 1/2inch Titanium coated

- Material:HSS4241,Titanium coated
- Drills from1/8 in to 1/2 in (1/8"-3/16"-1/4"-5/16"-3/8"-7/16"-1/2")



P09Y173 3pc Step Drill Set

- Material:HSS4241,Titanium coated
- Included:
- 1/8"—1/2",13 steps: 1/8", 5/32", 3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8", 13/32", 7/16", 15/32", 1/2"
- 1/4"—3/4", 9 steps: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4"
- 3/16"—1/2",6 steps: 3/16", 1/4", 5/16", 3/8", 7/16", 1/2"
- Quick-change 1/4" hex shan



P09Y222 13pc Left-hand Drill Bit Sets

- Material Science: speed steel 4241
- Surface treatment:Roast yellow
- Heat treatment
- Iron box:black
- Specifications:1/4",15/64",7/32",13/64", 11/64",5/32",9/64",1/8",7/64",3/32",5/64", 7/16"



P09Y871 6pc Annular Cutter Kit

- Shank Design: Weldon,
- Cutting Depth: 1"
- 1x 9/16" annular bit
- 1x 5/8" annular bit
- 1x 11/16" annular bit
- 1x 13/16" annular bit
- 1x 15/16" annular bit
- 1x 1-1/16" annular bit
- 1x Pilot Bits
- HSS Steel



P09Y174 3pc Step Drill Set

- Material:HSS4241,Titanium coated
- Included:
- 4-12mm(5 Step: 4mm, 6mm, 8mm, 10mm, 12mm)
- 4-20mm(9 Step: 4mm, 6mm, 8mm, 10mm, 12mm, 14mm, 16mm, 18mm, 20mm)
- 4-32mm(15 Step: 4mm, 6mm, 8mm, 10mm, 12mm, 14mm, 16mm, 18mm, 20mm, 22mm, 24mm, 26mm, 28mm, 30mm, 32mm)
- Quick-change 1/4"hex shank.



P09Y623 Quick Change Hex Socket Extension and Angled Bit Holder

- Adjustable 360° thumb flange
- 1/4 in. hex drive
- Durable die cast construction
- Length:315mm.
- Weight:300g



P09Z018B 3/8" 2 IN 1 12V 1300mAh Li-ion Cordless Drill & Driver

- Rechargeable battery: 12V 1300mAh Li-ion
- 2 speed Switchable: 0-400/0-1400rpm
- Charging Time: 1hours.BS
- Switch: Forward/Reverse
- Torque Grade: 18+1
- Quick-changing chuck: 10mm
- Max torque setting: 20Nm
- CE/GS approved



P09Y175 5pc HSS step drill set

- Material:HSS4241,Titanium coated
- Included:
- 3/8" shank: 11/4" to 1-3/8" 10 Steps (1/4", 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-3/8")
- 3/8" shank: 3/16" to 7/8" 12 Steps (1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8")
- 3/8" shank:1/4" to 3/4" 9 Steps (1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4")
- 1/4" shank:1/8" to 1/2" 13 Steps (1/8", 5/32", 3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8", 13/32", 7/16", 15/32", 1/2")
- 1/4" shank:3/16" to 1/2" 6 Steps (3/16", 1/4", 5/16", 3/8", 7/16", 1/2")



P09Y875 9pc HSS Annular Cutter Set

- Shank Design: Weldon
- Cutting Depth: 2"
- 1x 1/2" annular bit
- 1x 9/16" annular bit
- 1x 11/16" annular bit
- 1x 3/4" annular bit
- 1x 13/16" annular bit
- 1x 7/8" annular bit
- 1x 15/16" annular bit
- 1x 1-1/16" annular bit
- 1x 5/8" annular bit
- 2x Pilot Bits
- HSS:M2AL



P09Z023B 3/8" 2 IN 1 12V 1300mAh Li-ion Cordless Drill & Driver

- Rechargeable battery: 12V 1300mAh Li-ion
- 2 speed Switchable: 0-400/0-1400rpm
- Charging Time: 1hours
- Switch: Forward/Reverse
- Torque Grade: 18+1
- Dual Function with 3/8" Drill chuck and 1/4" Bit driver
- Max torque setting: 28Nm (1.5,2.5,3,4,5,6) 1pc adaptor
- CE/GS approved



P11Z011 Animal Shear 320W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power : 320W
- Electric Wire Length: 5m
- Suitable for sheep certification. The main components such as the plug, electric cable and switch have the certificate.
- Length measured from blade top to end of the body: 34.5 cm
- CE/GS approved



P15B031 7" Electric Cut-O Saw 1280W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- 7inch(180mm) TCT blade cuts slow and cold without the need for coolant fluid.
- Will handle steel, wood, brass, aluminium and most plastics, without the need to change blades.
- Even hidden nails/screws in timber are no longer a problem
- CETLus/GS approved



P11B035 Electric Nibbler 625W 2.5mm

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 625W
- Cutting thickness(mm):Sheet steel: 2.5
- Stainless steel: 1.5 mm
- Minium cuting radius(mm): 25
- Output Speed(RPM): 1000
- Cable length:2M
- CE/GS approved



P15B011 7" Electric Cut-O Saw 650W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 650W
- No Load Speed: 8800r/min
- Cutting Wheel Dia.: 7 inch(160MM)
- Guide plate adjusts 45 degrees left and right
- Spindle Lock,Quick Release Vise
- CETLus/GS approved



P15B041 14" Cut-o Saw 1800w

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1800W
- No-Load Speed: 3800rpm
- Disc Size:355mm
- Max Cut: Ø120mm.
- Cutting Capacity: 0°-90° Round pole:Ø120mm,Square bar: 70*70mm,Rectangle bar: 45*180mm, L bar:100*100mm
- Cutting Capacity: 0°-45° Round pole:Ø70mm, Square bar:60*60mm, Rectangle bar: 60*105mm
- L bar:50*50mm
- cETLus/GS approved



P11B037 Electric Nibbler 625W 3mm

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 625W
- Cutting thickness(mm):Sheet steel: 3
- Stainless steel: 1.2 mm
- Minium cuting radius(mm): 150
- Output Speed(RPM): 1000
- Cable length:2M
- CE/GS approved



P15B013 7" Abrasive Cut O Machine 660W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 660W
- No Load Speed: 5000r/min
- Disc Dia.: 160/180mm
- Guide plate adjusts 45 degrees left and right
- Spindle Lock,Quick Release Vise
- cETLus/GS approved



P15B051 14" Cut-off Saw 2000w

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 2000W.
- No-Load Speed: 3800rpm.
- Disc Size: 355mm.
- Max Cut: Ø120mm.
- Cutting Capacity: 0°-90°
- Round pole: Ø120mm, Square bar: 70*70mm, Rectangle bar: 45*180mm,
- L bar: 100*100mm.
- Cutting Capacity: 0°-45°
- Round pole: Ø70mm, Square bar: 60*60mm, Rectangle bar: 60*105mm,
- L bar: 50*50mm
- cETLus/GS approved



P17X040 40 pc Rotary Tool Kit

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No Load Speed: 8,000 ~ 30,000 RPM.
- Flexible Shaft.
- Height Adjustable Stand.
- 40 piece Assorted Accessories Included
- cETLus/GS approved



P17X055 40PCS Rotary Tool Kit

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load Speed: 8000-30000RPM
- 1.8m cable
- Accessories: 40pcs
- CETLus/GS approved



P17X035 80PCS Rotary Tool Kit

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load Speed: 8000-30000RPM
- 1.8m cable
- 80pcs accessories:
- CULus/GS approved



P17X043 152PCS Rotary Tool Kit

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load Speed: 8000-30000RPM
- 1.8m cable
- 152pcs accessories
- CETLus/GS approved



P17X057 43PCS Rotary Tool Kit

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load Speed: 8000-30000RPM
- 1.8m cable
- Accessories: 40pcs
- CETLus/GS approved



P17X037 35PCS Rotary Tool Kit

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load Speed: 10000-32000RPM
- 1.83m cable
- 35pcs accessories
- CETLus/GS approved



P17X045 250PCS Rotary Tool Kit

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No-load Speed: 8000-35000RPM
- Rated Input Power: 160W
- 1.8m cable
- 250pcs accessories
- CETLus/GS approved



P17X059 43PCS Rotary Tool Kit

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load Speed: 8000-30000RPM
- 1.8m cable
- Accessories: 40pcs
- CETLus/GS approved



P17X065 7.2V NI-CD 600mAh Cordless Rotary Tool

- Battery: Ni-CD 600mAh
- Charger Output Voltage: 7.2V DC
- Charger time: 3hours
- No-load speed: 5000-25000r/min
- CULus charger/GS approved



P19A143 Oscillating Multi-Tool 200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Oscillations: 20000opm
- Oscillation Angle: 3°
- Rated Input Power: 200W
- CETLus approved



P19A425 18V 1500mAh Li-ion Cordless Multi-function Tool

- Power Pack Capacity: 1.5Ah (Li-ion)
- No Load Speed: 5000-18000/min
- Oscillations Angle: 3°
- 1hour quick charger
- CE/GS/UL charger approved



P17X067 9.6V NI-CD 700mAh 42PCS Cordless Rotary Tool Kit

- Battery: Ni-CD 700mAh
- Charger Output Voltage: 9.6V DC
- Charger time: 3hours
- Accessories: 40pcs/Flexible shaft
- No-load speed: 5000-25000r/min
- CULus charger/GS approved



P19A335 10.8V 1500mAh Li-ion Cordless Multi-function Tool

- Power Pack Capacity: 1.5Ah (Li-ion)
- No Load Speed: 5000-18000/min
- Oscillations Angle: 3°
- 1hour quick charger
- CE/GS/UL charger approved



P21A235 Electric Router 8mm 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load speed: 10000-28000 r/min
- Collet Capacity: 8mm.
- VDE plug with 2m cable
- FADE brand speed adjustment switch
- Soft grip handles
- Variable speed
- CE/GS approved



P19A135 Oscillating Multi-Tool 180W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Voltage/Frequency: 120V/60Hz
- Oscillations: 20000opm
- Oscillation Angle: 2.8°
- Rated Input Power: 180W
- CETLus approved



P19A375 14.4V 1500mAh Li-ion Cordless Multi-function Tool

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 380W
- No load speed: 3000rpm
- Chuck size: 10mm, Reversible
- UL charger/GS approved



P21A236 Electric Router 8mm 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load speed: 10000-28000 r/min
- Collet Capacity: 8mm
- VDE plug with 2m cable
- FADE brand speed adjustment switch
- Variable speed
- CE/GS approved



P21A237 Electric Router 8mm 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No load speed:10000-28000 r/min
- Collet Capacity:8mm
- VDE plug with 2m cable
- FADE brand speed adjustment switch
- Variable speed
- CE/GS approved



P21G135 Jig Saw 3A

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated current: 3A
- No load speed: 3000r/min
- Cutting capacity: 2.15 inches
- Accessories:
- 1pc wrench, 1pc saw blade
- Cord length: 2m
- CETLus/GS approved



P23A135 Marble Cutter 110MM 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 1200W
- Max Impact Rates: 12000r/min
- UL/CE approved



P21E135 4 Speed Wood Lathe 1/2HP

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1/2HP, 2.9A
- Max.Cutting Diameter: 350mm
- Max.Cutting Length: 1000mm
- 4 speed(1100/1600/2300/3400RPM)
- CE/GS approved



P21W135 Deluxe Router Table

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Main Table(Aluminum): 335×450mm
- Extension Table(Steel): 335×200mm
- Inner Carton: 470×150×350mm
- Outer Carton: 622×490×390mm
- CE/GS approved



P23C237 Wall Chaser Machine 1700W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Input power: 1700W
- No-Laod speed : 4000/min
- Disc size: Ø150mm
- Cutting depth(mm): 10-40
- Cutting width(mm): 14/19/29
- Soft grip, With Soft Start, with Overload protection With Laser
- 2 Pcs Diamond Disc on the Machine
- BS Plug 1.8 m Cable(H05VV-F 2x1mm2)
- GS/CE approved



P21F237 Dust Collector 750W(1HP)

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power 750W(1HP).
- Fan diameter 230mm.
- Inlet diameter 100mm.
- NO.of intake holes 1×100.
- Air speed-50Hz 500CFM/14.15m3/min.
- Air speed-60Hz 600CFM/16.98m3/min.
- Bag diameter 370mm.
- Bag height 640mm.
- Bag volumn 0.057m3
- CE/GS approved



P23D133 1-1/2"" SDS Rotary Hammer Drill 800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 800W
- No-load speed: 0-800r/min
- Impact Speed: 3000Bpm
- With 2.2m Cord
- Accessories1 pc: 14x250mm Point Chisel , 1 pc: 14x250mm Point Chisel ; 1 pc: 14x250mm Flat Chisel ; 3 pcs: 6in-long Drills: 8mm/10mm/12mm ; 1 pc: 1/2"(13mm) Drill Chuck w/ SDS plus shank
- GS/CE approved



P23D135 1-1/2" SDS Rotary Hammer Drill 800W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1000W
- No-load speed: 780r/min
- Impact Speed: 4000/min
- Accessories1 pc: 14x250mm Point Chisel , 1 pc: 14x250mm Point Chisel ; 1 pc: 14x250mm Flat Chisel ; 3 pcs: 6in-long Drills: 8mm/10mm/12mm ; 1 pc: 1/2"(13mm) Drill Chuck w/ SDS plus shank
- GS/CE approved



P23D239 Demolition Hammer 1050W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 1050W
- Max Impact Rates: 2900/min
- Max Impact Joules: 10J
- GS/CE approved



P23E150 Electric Demolition Hammer 1500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No Load Speed: 1700BPM
- Motor power:1500W
- Accessories: 1pc hex point chisel, 1pc hex flat chisel,3pcsocket head wrench, 1pc wrench,1pc oilcan
- GS/CE approved



P23D139 Demolition Hammer 1050W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 1050W
- Max Impact Rates: 2900/min
- Max Impact Joules: 10J
- GS/CE approved



P23E124 Electric Demolition Hammer 1240W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- No Load Speed: 1400BPM
- Motor power: 1240watts
- Accessories: 1pc hex point chisel,1pc hex flat chisel,3pcsocket head wrench, 1pc wrench,1pc oilcan
- GS/CE approved



P23E153 Electric Demolition Hammer 1500W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max Impact Rates: 1900/min
- Motor power:1500W
- Accessories:1pc hex point chisel, 1pc hex flat chisel,3pc socket head wrench,1pc wrench,1pc oilcan
- GS/CE approved



P23D143 Demolition Hammer 1200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 1200W
- Max Impact Rates: 2900/min
- Max Impact Joules: 10J
- GS/CE approved



P23E127 Electric Demolition Hammer 1240W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max Impact Rates: 1900/min
- Motor power:1240W
- Accessories: 1pc hex point chisel, 1pc hex flat chisel,3pc socket head wrench,1pc wrench,1pc oilcan
- GS/CE approved



P23E160 Electric Demolition Hammer 1600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor power: 1600W
- No Load Speed: 1500BPM
- Accessories:1pc hex point chisel, 1pc hex flat chisel,2pc socket head wrench, 1pc wrench,1pc oilcan
- GS/CE approved



P23E170 Electric Demolition Hammer 1700W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor power: 1700W
- No Load Speed: 1500BPM
- Accessories: 1pc hex point chisel, 1pc hex flat chisel, 2pc socket head wrench, 1pc wrench, 1pc oilcan
- GS/CE approved



P23I147 Electric Mixer 1400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Input power: 1400W.
- No load speed: I: 180-380(min), II: 300-650(min).
- Number of gears: 2.
- Tool fitting/Clamp thread: M14 x 2.
- Protective type/protective class: Double insulation/II.
- Mixing paddle diameter: 140mm.
- CE/GS approved



P23J235 Electric Cement Mixer 50L 375W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power 375W S2 15min.
- Motor No-load Speed 1450rpm.
- Drum Speed 50rpm.
- Drum Capacity 50L.
- Diameter of Drum 420mm.
- Diameter of Drum Opening 270mm.
- Punched gear ring.
- CE/GS/CSA approved



P23E250 Electric Demolition Hammer 230V 2200W

- Voltage: 230V/50Hz
- No Load Speed: 1700BPM
- Motor power: 2200W
- Accessories: 1pc hex point chisel, 1pc hex flat chisel, 3pc socket head wrench, 1pc wrench, 1pc oilcan,
- CE/GS Certificated



P23J135 Electric Cement Mixer 35L 325W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor No-load Speed 1750rpm
- Drum Speed 35rpm
- Drum Capacity 35L
- Diameter of Drum 16.5"
- Diameter of Drum Opening 10"
- Drum thickness: up/lower drum 1.2/1.2 mm
- Punched gear ring
- CE/GS/CSA approved



P23J255 Electric Cement Mixer 140L 550W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor No-load Speed 2950rpm.
- Drum Speed 34rpm.
- Drum Capacity 140L.
- Diameter of Drum 560mm.
- Diameter of Drum Opening 375mm.
- Drum thickness: up/lower drum 1.2/1.8 mm.
- Cast iron gear ring.
- Overall denmision: 1160x670x1330mm
- CE/GS approved



P23G135 Portable Concrete Vibrator 465W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Input Power: 465W
- Vibrations Per Minute (VPM): 12000
- No-Load Speed: 3300 r/min
- Vibrator Shaft(in.): 40"
- Overall Length (in.): 45"
- Shaft Diameter (in.): 1.476"
- CE approved



P23J153 Electric Cement Mixer 100L 420W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor No-load Speed 1750rpm
- Drum Speed 36rpm
- Drum Capacity 100L
- Diameter of Drum 22"
- Diameter of Drum Opening 15"
- Drum thickness: up/lower drum 1.2/1.8 mm
- Punched gear ring
- CE/GS/CSA approved



P23K035G Gasoline Engine Rotary Sieving Machine 1/2 HP

- Powerful: 1/2 HP
- Engine type: single cylinder air cooling 2-cycle gasoline engine
- Fuel used: lubricating oil mixed gasoline (mixing rate: 40: 1)
- Lubricating oil used: 2-cycle engine oil
- Fuel tank capacity: 0.5L
- Each tank working time: 2 hours
- Drum rotation: 45 RPM
- Drum diameter: 375mm
- Drum length: 785mm
- Diameter of external sieve: 2cm
- EPA approved



P23Y015 17PCS SDS Drill Bit Set

- 12 x SDS drills 2 x SDS drills 110 mm (5 – 6)
- 7 x SDS drills 160 mm (5 – 5.5 – 6 – 6.5 – 7 – 8 – 10)
- 3 x SDS drills 260 mm (10 – 12 – 14)
- 1 X SDS drill 210MM (14)
- 2 x flat chisels 14 x 250 x 20 mm
- 14 x 250 x 40 mm
- 2 x pointed chisels 14 x 250 mm
- 14 x 250 mm
- YG8C Alloy steel blade, full heat treated, sand blasted surface



P23K135 Electric Motor Rotary Sieve Sieving Machine 360W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated power: 360W
- Rated power under load: 180W
- Drum rotation: 45RPM
- Dimensioning expanded: 1080*652*1350mm
- Drum diameter: 375mm
- Drum length: 785mm
- Diameter of external sieve: 2cm
- Diameter of inner sieve: 1cm
- Noise: 89db
- CE approved



P23Y011 10PCS SDS Drill Bit Set

- 5mm, 6mm, 8mm x 110mm, 10mm, 12mm x 160mm, 14mm, 16mm x 210mm, 18 x 360mm
- Flat Chisel 20mm x 250mm, Point chisel 250mm,
- YG8C Alloy steel blade, full heat treated, sand blasted surface



P23Y019 17PCS SDS Drill Bit Set

- 12 x SDS drills
- 4 x SDS drills 110 mm (5 – 6 – 8 – 10)
- 4 x SDS drills 160 mm (6 – 8 – 10 – 12)
- 2 x SDS drills 210 mm (8 – 10)
- 2 x SDS drills 260 mm (12 – 14)
- 3 x flat chisels 14 x 143 x 20 mm
- 14 x 250 x 20 mm 14 x 250 x 40 mm
- 2 x pointed chisels 14 x 143 mm
- 14 x 250 mm
- YG8C Alloy steel blade, full heat treated, sand blasted surface



P23Y013 11PCS SDS Drill Bit Set

- 3/16", 1/4", X 4"
- 1/4", 5/16", 3/8", X 6"
- 3/8", 1/2", X 8"
- 3/8", 1/2", 5/8", 3/4", X 18"
- 3/8" SDS (standard) shank size
- YG8C Alloy steel blade, full heat treated, sand blasted surface



P23Z025 1/2" 20V 3000mAh Li-ion Cordless Hammer Drill

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Power: 360W
- Rated Power under Load: 180W
- Drum Rotation: 45rpm
- Dimensioning Expanded: 1080*652*1350mm
- Drum Diameter: 375mm
- Drum Length: 785mm
- Noise: 89db
- IP44



P27A055G 33cc Gas Blower

- Displacement: 33CC
- Standard Power: 0.9/7500
- Form Of Carburetor: Diaphragm
- Mix fuel ratio: 40:1
- Tank capacity: 0.65
- Average Air Volum 0.2CBM/m
- EPA Approved



P27A135 Electric Blower 550W

- Rated Voltage/Frequency: 100V/50 or 100V/60Hz
- Rated Output: 550W
- No-load Speed: 0-13000RPM
- Air Flow: 2.8 CBM/Min
- Accessory: Dust bag, Blowpipe, Carbon brush
- PSE approved



P27B521B 3.6V 3 in 1 Cordless Grass & Shrub Shear

- Power Pack Capacity: 1.3Ah (Li-ion)
- Charge time: 3-5 hours
- Running time: 60 mins
- CE approved



P27A065G 42.7CC Gasoline Backpack Leaf Blower

- Flow(m³/s): 0.2.
- Air Speed(m/s): 70.
- Standard Power(kw):1.25.
- Displacement(cc): 42.7.
- Carburetor Type: Diaphragm.
- Igniting Mode: No Touch.
- Method of Start: Recoil Starting.
- Mixed Fuel Ratio: 25: 1.
- Max. motor speed: 7000r/min.
- Tank capacity: 1.2L.
- Acoustic pressure (Lpa): 95,1 dB(A) (K= 3 dB(A)).
- Acoustic power(Lwa): 105 dB(A) (K= 1,99 dB(A))



P27B532B 3.6V 3 in 1 Cordless Grass & Shrub Shear With Rotation Handle

- Power Pack Capacity: 1.3Ah (Li-ion)
- Charging time: 3-5 hours
- Using time: 30-40 mins
- CE approved



P27B536B 3.6V 3 in 1 Cordless Grass & Shrub Shear With Rotation Handle

- Power Pack Capacity: 1.3Ah (Li-ion)
- Charging time: 3-5 hours
- Running time: 40-45 mins
- CE approved



P27A130 Electrical Leaf Blower 3000W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Input power:3000W.
- No load speed:5000~13000rpm.
- Wind volume:13m³/min.
- Max wind speed:210km/h.
- Max shredder ratio:10:1.
- Collection capacity:30L
- CE/GS approved



P27B535B 3.6V 3 in 1 Cordless Grass & Shrub Shear

- Power Pack Capacity: 1.3Ah (Li-ion)
- Charging time: 3-5 hours
- Running time: 40-45 mins
- CE approved



P27C011G 23CC Grass Trimmer

- Gasoline Engine: 1E32F
- Fuel Mixture Ratio: 1:25
- Displacement: 22.5CC
- Ignition: CDI
- Power: 1.0 KW
- Shaft diameter: 26mm
- Shaft Length: 1500mm bent shaft
- CE/GS approved



P27C013G 33CC Grass Trimmer

- Gasoline Engine: 1E36F
- Fuel Mixture Ratio: 1:25
- Displacement: 32.6CC
- Ignition: CDI
- Power: 1.2 KW
- Shaft diameter: 26mm
- Shaft Length: 1530mm
- Head: nylon cutter + 3T blade
- CE/GS approved



P27C023G 25CC Grass Trimmer 2-stroke 415mm

- Engine type: 2-stroke
- Displacement: 25cc
- Max power:0.7kw/8000r
- Cutting width:415mm
- Big spool and 3T blade
- Gear case and clutch comp.
- "G"handle",Two section,Straight pipe
- Simple single shoulder harness
- EPA approved



P27C113G 31CC Grass Trimmer 4-stroke 345mm

- Engine type: 4-stroke
- Displacement: 30.5cc
- Max power:0.55kw/7000r
- Cutting width:345mm
- Small spool
- No gear case
- Loop handle,Two section,Flexual pipe
- EPA approved



P27C015G 43CC Grass Trimmer

- Gasoline Engine: 1E40-5F
- Fuel Mixture Ratio: 1:25
- Displacement: 42.7CC
- Ignition: CDI
- Power: 1.6 KW
- Shaft diameter: 26mm
- Shaft Length: 1530mm
- Head: nylon cutter + 3T blade
- CE/GS approved



P27C045G 52cc Brush Cutter

- Power: 1.65kw/6500rpm
- Displacement: 52cc 2-Stroke, Engine : 1E44F-5
- Fuel tank capacity: 1200ml
- Fuel:gasoline 25:two cycle oil 1
- Working pole length: 1650mm
- Pole diameter:26mm
- CE/GS approved



P27C911G 4 in 1 Grass Trimmer 1.65KW 52cc

- Gasoline Engine: 1E34F
- Fuel Mixture Ratio: 1:25
- Displacement: 26.3CC
- Ignition: CDI
- Power: 1.0 KW
- Shaft diameter: 26mm
- Shaft Length: 1530mm
- Head: nylon cutter + 3T blade + chain saw + hedge trimmer + lengthen bar
- CE/GS approved

P27C021G 25CC Grass Trimmer 2-stroke 375mm

- Engine type: 2-stroke
- Displacement: 25cc
- Max power:0.7kw/8000r
- Cutting width:375mm
- Small spool
- No gear case
- Loop handle,Two section, Flexual pipe
- Homemade magnetor
- Homemade carburetor
- EPA approved



P27C111G 25CC Grass Trimmer 4-stroke 415mm

- Engine type: 4-stroke
- Displacement: 24.5cc
- Max power:0.7kw/8000r
- Cutting width:415mm
- Big spool and 3T blade
- Gear case and clutch comp.
- "G"handle,Straight pipe, Simple single shoulder harness
- EPA approved



P27C923G 4 in 1 Grass Trimmer 1.65KW 52cc

- Engine model:1E44F-5
- Displacement:52cc
- Power type:Single Cylinder, Two-stroke,Air-cooling,gasoline engine
- Rated output power:1.65KW
- Fuel tank capacity:1200ml
- Gasoline/2-cycle oil mixing ratio:25:1
- Pipe diameter:26mm/28mm
- CE/GS approved



P27D015G 4HP 20" Gasoline Lawn Mower (Self-propelled)

- Max. Power: 4.0 HP
- Displacement: 158CC
- Start Way: recoil
- Drive type: self-propelled
- Idle speed: 2700 rpm
- Cutting width: 510 mm (20 inch)
- Cutting height: 30-80 mm, 10 lever adjustment
- Height adjustment: 1 lever adjustment
- Wheel diameter: Front:8inch;Rear:10inch
- Grass bag capacity: 60 L
- CE/GS approved



P27D011G 4HP 18" Gasoline Lawn Mower (Hand Push)

- Max. Power: 4.0 HP
- Displacement: 123CC
- Start Way: recoil
- Drive type: hand push
- Idle speed: 2800 rpm
- Cutting width: 460 mm (18 inch)
- Cutting height: 25-70 mm, 10 adjustment
- Height adjustment: 1 lever adjustment
- Wheel diameter: Front:8inch;Rear:10inch
- Grass bag capacity: 60 L
- CE/GS approved



P27D025G 6HP 22" 4 in 1 Gasoline Lawn Mower (Self-propelled)

- Max. Power: 6.0 HP
- Displacement: 173CC
- Start Way: recoil
- Drive type: self-propelled,
- 4 in 1 : grass cut, grass mill, side discharge, back discharge
- Idle speed: 2800 rpm
- Cutting width: 560 mm (18 inch)
- Cutting height: 30-90 mm, 7 lever adjustment
- Height adjustment: 1 lever adjustment
- Wheel diameter: Front:8inch;Rear:10inch
- Grass bag capacity: 65 L, light weight plastic structure
- CE/GS approved



P27D013G 4HP 18" Gasoline Lawn Mower (Self-propelled)

- Max. Power: 4.0 HP
- Displacement: 135CC
- Start Way: recoil
- Drive type: self-propelled
- Idle speed: 2800 rpm
- Cutting width: 460 mm (18 inch)
- Cutting height: 25-70 mm, 10 adjustment
- Height adjustment: 1 lever adjustment
- Wheel diameter: Front:8inch;Rear:10inch
- Grass bag capacity: 60 L
- CE/GS approved



P27E011G 26CC Hedge Trimmer

- Gasoline Engine: 1E34F
- Displacement: 26.3CC
- Power: 1.0 KW
- Cutting capacity: 23mm dia
- Cutter length: 600mm
- Accessories: tool kit
- CE/GS approved



P27E012G 26CC Hedge Trimmer

- Engine: 1E34F
- Displacement: 26.3CC
- Power: 1.0 KW
- Cutting capacity: 23mm dia
- Cutter length: 560mm
- Accessories: tool kit
- CE/GS approved



P27F135 Electric Chipper Shredder 2.5HP

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Power: 14A
- Cutting Capacity: 1-1/2 inch
- Horse Power: 2.5HP
- Maximum Speed: 4300 RPM
- Blade size: 7inch
- CE/GS/CSA approved



P27H055 43CC Auger Power Head

- Displacement : 43CC
- Mix fuel ratio : 40:1
- Reduction Ratio: 40:1
- Bit Diameter : 150mm
- Tank capacity 0.98L
- Standard Power : 1.3/7500 (KW/r/min)
- CE/GS/EPA approved



P27F155 Electric Chipper Shredder 2.5HP

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Consumption power P1: S2: 30min. - 2.5HP
- Revolution 1/min: 3450RPM
- Switch: Rocker switch with safety key
- Power Cord Length/Plug: 6' UL SJT power cord and plug
- Infeed opening max: 30 * 160mm
- Wheel diameter: 165mm
- CE/GS/CSA approved



P27I135 Log Splitter - 5ton

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor No-load speed 3450rpm
- Insulation class Class B
- Protection degree IP 54
- Max.splitting force 5 tons
- Max.cylinder travel 390mm
- Diameter of cylinder 55mm
- Length 520mm
- Hydraulic oil capacity 2.8L
- CE/GS/CSA approved



P27G045G 58cc Petrol Chainsaw

- Power: 2.2kw/8000rpm
- Displacement: 58cc, 2-stroke
- Fuel tank capacity: 550ml
- Oil tank capacity: 260ml
- Fuel:gasoline 25:two cycle oil 1
- Saw chain: 0.325"
- Standard bar type size: 20in
- Easy start
- CE/GS approved



P27I143 Log Splitter - 6ton

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor No-load speed 3450rpm
- Insulation class Class B
- Protection degree IP 54
- Max.splitting force 6 tons
- Max.cylinder travel 390mm
- Diameter of cylinder 60mm
- Diameter 50-250mm
- Length 520mm
- Hydraulic oil capacity 2.8
- CE/GS/CSA approved



P27I335 Log Splitter - 6ton

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor No-load speed 2950min-1
- Insulation class Class B.
- Protection degree IP 54.
- Max.splitting force 6 tons.
- Max.cylinder travel 390mm.
- Diameter of cylinder 60mm.
- Diameter 50-250mm.
- Length 520mm.
- Hydraulic oil capacity 2.8L
- CE/GS/CSA approved



P27I339 Log Splitter - 6ton

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor No-load speed 2950min-1.
- Insulation class Class B.
- Protection degree IP 54.
- Max.splitting force 6 tons.
- Max.cylinder travel 390mm.
- Diameter of cylinder 60mm.
- Diameter 50-250mm.
- Length 520mm.
- Hydraulic oil capacity 2.8
- CE/GS/CSA approved



P27I735D Hydraulic Log splitter 22T Diesel Engine

- Speeco's 22 ton log splitter is equip with a Briggs and Stratton 10.5hp engine to deliver maximum splitting force.
- A global leader in log splitting technology, Speeco offer the best features in the industry.
- This splitter will make log splitting safer,faster and easier than before



P29A025 1350W Electric Pipe Threading Machine

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor: 1200-1350w universal type
- Speed: 18-28 RPM for threading, 51RPM reverse
- Die head: 1/2", 3/4", 1", 1 1/4", 1 1/2", 2"(Type 11R) 9Cr-2 Steel or HSS Steel Optional
- Gear Housing: Aluminum
- Standard equipment including: carrying case
- CE/CSA approved



P29A035 1400W Electric Pipe Threading Machine

- Rated Voltage/Frequency:120V-60Hz / 230V-50HZ
- Power: 1400W
- Principal Axis Rotate Speed: 26 (r/min)
- Accessory: Screw Die:1SET(4PCS)1/2", 3/4",1",1-1/4"(Cast Steel)
- CE/cETLus approved



P29A055 1700W Electric Pipe Threading Machine

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Die head material: 9Cr2
- No-Load Speed:23r/min
- Thread pipe from 1/2" to 1 1/4
- Includes 4 cast iron dies: 1/2", 3/4", 1", 1 1/4",1 1/2",2" Pipe clamp
- Pipe clamp blade:alloy steel
- CE/GS approved



P29A073 2000W Electric Pipe Threading Machine

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 2000W
- Principal Axis Rotate Speed: 28 (r/min)
- Weight: 7kg
- Accessory: Screw Die:1SET(4PCS)1/2", 3/4",1",1-1/4"(Cast Steel),
- CE/GS/CETLus approved



P31A135 1500W Gasoline Generator

- Rate AC Output: 1.2KW
- Max. AC Output:1.5KW
- Frenquency: 60HZ Voltage: 110-120V
- DC:12V 8.3A,Voltage Regulator: Condenser
- Φ19mm Steel Tube
- Noise level (7m): 63-65dB(A)
- Power Factor: Cosφ=1.0
- Cont. working time: 6-7h
- 2.8HP Air-cooled, 4 stroke,OHV, single cylinder
- Fuel tank capacity: 5.5L
- Fuel consumption: ≤450g/KW-hour
- Engine Oil Capacity: 0.4L
- Recoil and hand-operated
- EPA/CARB approved



P29A093 2300W Electric Pipe Threading Machin

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- 3HP(2300W) motor
- Die head material: 9Cr2
- No-Load Speed:23r/min
- Thread pipe from 1/2" to 1 1/4
- Includes 4 cast iron dies: 1/2", 3/4", 1", 1 1/4",1 1/2",2" Pipe clamp
- CE/GS approved



P31A145 3500W Gasoline Generator

- Rechargeable battery: 12V/1*1300mAh Li-ion
- No-load speed: 0-400/0-1400rpm
- Charge time: 1 hours fast charger
- Max Torque: 18 N.m /28N.m
- Switch:Forward/Reverse
- Chuck: 1/4",
- LED working light,Belt hooks
- Clutch:18+1 setting
- CE/GS/EMC/RoHS approved



P31A022 1200W Gasoline Generator

- A.C.freQUENCY: 60Hz
- Max.A.C.output: 900VA .
- Rated A.C.output: 800VA
- Work capacity: 63CC
- Ignition system: CDI
- Starting system: Recoil
- Fuel tank capacity: 4.2Liter
- Continuous operating time: 6hour
- 1-cylinder,2-stroke, Air-cooled gasoline engine
- EPA approved



P31B015 1000W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- D. C. Output: 12V 5A
- Rated power output(KW): 0.9
- Max. power output(KW): 1.0
- Displacement: 53cc
- Bore*Stroke(mm): 43.5X35.8mm
- Ignition system: T.D.I
- Fuel tank capacity: 3.5L
- Continue operating hour: 6
- CE/GS/CSA/EPA/CARB approved



P31B018
1200W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Ignition system: T.D.I
- Fuel tank capacity: 3.5L
- Continue operating hour: 4
- Noise (7m away): 58dba
- Starting System: Recoil
- Forced Air-Cooled, 1-Cylinder, 4-Stroke, OHV
- CE/GS/CSA/EPA/CARB approved



P31B025
2000W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- D. C. Output: 12V 8A
- Rated power output(KW): 1.6
- Max. power output(KW): 2.0
- Displacement: 105cc
- Ignition system: T.D.I
- Fuel tank capacity: 4L
- Continue operating hour: 5
- Noise (7m away): 58dba
- Starting System: Recoil
- CE/GS/CSA/EPA/CARB approved



P31B027
2200W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- D. C. Output: 12V 8.3A
- Rated power output(KW): 2
- Max. power output(KW): 2.2
- Displacement: 125cc
- Bore*Stroke(mm): 52.4*57.8mm
- Ignition system: T.D.I
- Fuel tank capacity: 7L
- Continue operating hour: 6.
- CE/GS/CSA/EPA/CARB approved



P31B029
2600W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- D. C. Output: 12V 8.3A
- Rated power output(KW): 2.3
- Max. power output(KW): 2.6
- Displacement: 125cc
- Bore*Stroke(mm): 52.4x57.8mm
- Ignition system: T.D.I
- Fuel tank capacity: 7L
- CE/GS/CSA/EPA/CARB approved



P31B035
3300W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- D. C. Output: 12V 8.3A
- Rated power output(KW): 3.0
- Max. power output(KW): 3.3
- Displacement: 149cc
- Bore*Stroke(mm): 57.4x57.8mm
- Ignition system: T.D.I
- Fuel tank capacity: 7L
- CE/GS/CSA/EPA/CARB approved



P31B045
3500W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- D. C. Output: 12V 8.3A
- Rated power output(KW): 3
- Max. power output(KW): 3.5
- Displacement: 270cc
- Bore*Stroke(mm): 77*58mm
- Ignition system: T.D.I
- Fuel tank capacity: 13L
- CE/GS/CSA/EPA/CARB approved



P31B052
1200W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max. AC Output: 1200w
- Rated AC Output: 1000w
- DC Output: 12V/4A
- Type: Forced Air-cooled, 4-stroke, OHC
- Fuel Tank Capacity: 3.6L
- CE/GS/CSA/EPA/CARB approved



P31B060
2000W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rated Amperage: 4.2A
- Rated Input Power: 500W
- No load speed: 3000rpm
- Chuck size: 10mm, Reversible
- CETLus/GS approved



P31E011
Gasoline Engine Series 3.0kW

- Maximum power: 3.0kW (5.5HP)/3,600rpm
- Engine type: Single-Cylinder, 4 stroke, air cooling . OHV
- Fuel tank capacity: 1US gallons (3.6L)
- Oil Capacity: 0.6L
- Horizontal shaft
- Start system: Recoil



P31B055
1500W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max. AC Output: 1500w
- Rated AC Output: 1200w
- DC Output: 12V/4A
- Type: Forced Air-cooled, 4-stroke, OHC
- Fuel Tank Capacity: 3.6L
- CE/GS/CSA/EPA/CARB approved



P31B065
2500W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max. AC Output: 2500w
- Rated AC Output: 2200w
- DC Output: 12V/ 5 A
- Type: Forced Air-cooled, 4-stroke, OHC
- Fuel Tank Capacity: 5 . 1 L
- CE/GS/CSA/EPA/CARB approved



P31E015
Gasoline Engine Series 5.0kW

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max. AC Output: 2500w
- Rated AC Output: 2200w
- DC Output: 12V/ 5 A
- Type: Forced Air-cooled, 4-stroke, OHC
- Fuel Tank Capacity: 5 . 1 L
- CE/GS/CSA/EPA/CARB approved



P31B058
1800W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max. AC Output: 1800w
- Rated AC Output: 1500w
- DC Output: 12V/4A
- Type: Forced Air-cooled, 4-stroke, OHC
- Fuel Tank Capacity: 3.6L
- CE/GS/CSA/EPA/CARB approved



P31B075
3500W Gasoline Inverter Generators

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max. AC Output: 3500w
- Rated AC Output: 2800w
- DC Output: 12V/8.3A
- Type: Forced Air-cooled, 4-stroke, OHC
- Fuel Tank Capacity: 5 . 1 L
- CE/GS/CSA/EPA/CARB approved



P31E019
Gasoline Engine Series 7.08kW

- Maximum power: 7.08kW (13HP)/3,600rpm
- Engine type: Single-Cylinder, 4 stroke, air cooling . OHV
- Fuel Tank Capacity : 6.5L
- Oil Capacity: 1.1L
- Horizontal shaft
- Start system: Recoil/Electric



P31E023 Gasoline Engine Series 7.5kW

- Maximum power: 7.5kW (15HP)/3,600rpm
- Engine type: Single-Cylinder, 4 stroke, air cooling . OHV
- Fuel Tank Capacity : 6.5L
- Oil Capacity:1.1L
- Horizontal shaft
- Start system: Recoil/Electric



P33A735D 12V DC Diaphragm Water Pump

- Voltage:12V DC 7A
- Max Flow: 2.5G/min
- Revolution: 1200r/min
- Max Pressure: 35PSI
- Suction: 5M
- Power: 40W
- Can run dry without damage
- Pump body material:Nylon66
- Copper wire motor



P33D019 Clear / Dirty Water Submersible Pump 1100W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- 1100 watt Motor
- 1-1/4" & 1-1/2" Discharge Fitting
- Oil Free Motor
- Thermal overload protection
- Thermoplastic construction
- Corrosion Resistant
- Drain Water down to 3/16" to surface



P33A135 Electric Water Pump 370w

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- SPEED:3450RPM
- 1" Inlet And 1" Outlet Threaded
- Q.max:32L/min
- 1.2M ELECTRIC cord UL Approved.
- Brass impeller
- Heavy Duty Steel and Aluminum Construction



P33D013 Clear / Dirty Submersible Water Pump 400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- SPEED:3450RPM
- 1" Inlet And 1" Outlet Threaded
- Q.max:32L/min
- 1.2M ELECTRIC cord UL Approved.
- Brass impeller
- Heavy Duty Steel and Aluminum Construction



P33D115 3300 GPH Stainless Steel Submersible Pump

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Rate power: 750W
- Cable length:26 feet
- MAX pump rate: 3,300GPH
- MAX grain size: 5mm
- Water temperature max: 95F
- Dia. de la tubería: 1" o 1-1/4"



P33A145 Electric Water Pump 750w

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- SPEED:3450RPM
- 1.5" Inlet And 1.5" Outlet Threaded
- Q.max:60L/min.
- 1.2 MELECTRIC cord UL Approved
- Brass impeller
- Heavy Duty Steel and Aluminum Construction



P33D017 Clear / Dirty Water Submersible Pump 900W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Flow 3700 GPH
- 900 watt Motor
- 1-1/4" & 1-1/2" Discharge Fitting
- Oil Free Motor
- Thermal overload protection
- Thermoplastic construction



P33D213 Submersible Pump 400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Max. Flow: 7500LPH.
- Max. Grain Size: 35MM.
- Dia. Of Pipe: 1"/1.25"/1.50".
- Certifications: ROHS/LVD/GS/CE/EMC.
- Power Line Length:10M.
- Corrosion Resistant.
- Thermal overload protection.
- Built in automatic float switch allows for both manual and automatic switching.



P33Z015 6.5HP Gasoline Water Pump

- Engine type: Single Cylinder 4stroke EPA PHASE III
- Cooling system: Forced air cooled
- Engine displacement(cc): 196cc
- Horse power: 6.5hp
- Maximum Discharge Head: 105 FT
- Maximum Suction Head: 28FT
- Maximum Pressure: 36PSI
- Sound rating(dB): 78dB Start type: Recoil Fuel Type:Gasoline
- EPA approved



P35D035 20" HV Floor Fan 150W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 150W.
- Full copper ball bearing motor.
- 3 Speed rotary speech.
- 3 Aluminum balanced blades.
- 120° Tilt angle.
- Spiral-shape, metal grill.
- Powder coated, balck finishing.
- Up to 3950 CFM
- GS/cETLus approved



P35E047 30" High Velocity Oscillating Pedestal Fan 220W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 220W.
- Full copper ball bearing motor.
- Speed rotary speech.
- Aluminum balanced blades.
- Electroplating.
- Pedestal material: cast iron.
- 2 Meter power line.
- Oscillating.
- Extendable tube.
- Adjustable tilt blowing angle.
- Up to 8828.7 CFM
- GS/cULus approved

P33Z017 7HP Gasoline Water Pump

- 7HP 4 Stroke Air Cooled Engine
- Displacement: 208CC
- Rated Output: 3600KW/RPM
- Flow Rate: 58m³/h
- Max Head: 28m
- Max Suction: 7.5m
- Engine Oil Capacity: 0.6L
- Fuel Tank Capacity: 3.6L
- Discharge connections: 3" NPT Inlet&Outlet
- EPA approved



P35E025 18" High Velocity Pedestal Fan 130W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 130W.
- Black finishing grills.
- 3 aluminum blades.
- 3 Speed setting control.
- Heavy duty base.
- Adjustable height.
- Up to 3000 CFM.
- GS/CETLus approved



P35D025 18" HV Floor Fan 150W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 150W.
- Full copper ball bearing motor.
- 3 Speed rotary speech.
- 3 Aluminum balanced blades.
- 120° Tilt angle.
- Spiral-shape metal grill.
- Powder coated, balck finishing.
- Up to 3422 CFM.
- GS/cETLus approved



P35E045 30" High Velocity Pedestal Fan 250W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 250W.
- Full copper ball bearing motor.
- 2 Speed rotary speech.
- 3 Aluminum balanced blades.
- Spray paint processing.
- Pedestal material: cast iron.
- 2 Meter power line.
- Can not oscillating.
- Extendable tube.
- Up to 8475.5 CFM.
- Adjustable tilt blowing angle
- GS/cULus approved



P35G014 24" Drum Fan 200W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 200W
- Outlet Diameter: 630mm
- Speed: 1050/850(r/min)
- Air Volume: 4000/3200(m³/h)
- Drive Way: Motor
- CETLus approved



P35G016 36" Drum Fan 380W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 380W
- Outlet Diameter: 950mm
- Speed: 600/500(r/min)
- Air Volume: 13300/9500(m³/h)
- Drive Way: Moto
- CETLus approved



P35G025 24" Drum Fan 220W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 220W
- Full copper ball bearing motor
- 2 Speed rotary speech
- 3 aluminum balanced blades
- Powder coated, balck finishing
- Portable with castors
- Up to 7769.2 CFM
- CULus approved



P35G027 24" Drum fan 220W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 220W
- Full copper ball bearing motor
- 2 speed rotary speech
- 3 aluminum balanced blades
- Powder coated, black finishing
- Portable with castors
- Up to 7769.2 CFM
- CULus approved



P35G035 36" Drum Fan 485W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 485W.
- Full copper ball bearing motor.
- 2 Speed rotary speech.
- 3 Aluminum balanced blades.
- Powder coated, balck finishing.
- Portable with castors.
- Up to 11300.7 CFM
- CULus approved



P35G037 36" Drum fan 455W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 455W
- Full copper ball bearing motor
- 2 speed rotary speech
- 3 aluminum balanced blades
- Powder coated, balck finishing.
- Portable with castors
- Up to 11200 CFM
- CULus approved



P35G045 42" Drum Fan 735W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 735W
- Full copper ball bearing motor
- 2 Speed rotary speech
- 4 Aluminum balanced blades
- Powder coated, balck finishing
- Portable with castors
- Up to 17728 CFM
- CULus approved



P97X021 9pc Bi-Metal Hole Saw Kit

- 9 Pcs set.
- Sizes: 3/4", 7/8", 1-1/8", 1-1/2", 1-3/4" and 2-1/4".
- Mandrels: 1/4" and 3/8".
- Drill bit: 1/4".



P99C173 Airless Paint Sprayer 600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor rating power:600W
- Max pressure:210Bar.
- Max (Fluid) delivery: 1100ml/min.
- Recommended spray distance:300mm.
- Fan Pattern Width:250-310mm.
- Standard nozzle size:517.
- Compressive strength and length of high pressure hose: 300Mpa/1M.
- 25Ft.hose for easy mobility when painting large surfaces.
- Body treatment:Powder Coating
- CETLus approved



P95X189 89pcs Impact Drill Kits

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- 1*13mm Impact Drill
- 1*115mm Angle Grinder
- 1*55mm JIG SAW
- Accessories:6pcs 25MM bit,1pc magnetic bit holder,3pcs twist drill,3pcs masonry drill,3pcs wood working drill,3pcs shank sanding stone,2pcs air blowing plastic case, 1pc wrench



P99A135B 18V 1500mAh Li-ion Cordless Riveter

- Voltage: 18V Li-ion 1500mAh
- Stroke: 19mm
- Max Working Force: 6000Nm
- Charger Time: 1 hour
- 4pcs nose piec:
1 x 4.8mm nose piece(fitted on body),
1 x 2.0mm,
- 1 x 3.0mm,1 x 4.0mm
- 1pc open spanner
- GS/CE approved



P99C235 Electric Spray Gun 400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 400W
- Spraying Pressure: 0.1-0.2Bar
- (Water) Flow Rate: 700ml/min
- Max. Viscosity: 60DIN-s
- Nozzle: Ø2.5mm
- Container Capacity: 800ml
- Quick release head
- CE/GS approved



P97X011 5 Pcs Jig Saw Jigsaw Blade set

- HCS (High Carbon Steel).
- Hole Dia 4mm.
- Working Length 65mm.
- Tooth Spacing 2.5mm.
- Length: 90mm



P99C135 Electric Hvlp Paint Sprayer 450W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Air pressure:0.1-0.2 BAR
- Cup Capacity:1000ml
- Max Fluid Delinery:230-270ml/min
- Nozzle Size:1.0mm
- Input volt : 120
- Power(w) :450
- Load Speed(R.P.M) 28500
- Load current(A): 4.2.



P99C273
Electric airless paint sprayer 400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power source: 400W
- Max delivery : 0.24GPM(1.0LPM)
- Max tip size: 0.017"
- Max operating pressure :2900PSI(200BAR)
- Working pressure : 120-170BAR
- Hose:7.5M HP hose
- Gun: 1XNA500B
- CE approved



P99E035
12V 1500mAh Li-ion Cordless Caulking Gun

- Battery: 12V, Li-ion 1*1500mAh.
- Power of thrust: 220KG Speed choose button.
- Max capacity: 600ml.
- 1 hours charger.
- Simple design,easy portable.
- Plastic box packing.
- For Cartridge and Sausage pack
- CE approved



P99D133
Powder Coating Sprayers

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Line Cord: 6 feet long, 0.75mm2, 3-prong grounded plug
- Air Supply Pressure: 10 to 30 PSI
- Cubic Feet Per Minute: 3.5 CFM at 30 PSI
- Air Inlet Size: 1/4 inch
- Remote Activation Switch: 8 Feet long
- Gun Powder Lead: 7 feet, high voltage lead
- Grounding Cable: 8 feet long with ground clamp
- Control Box Fuse: 0.5 amps
- Paint Curing Temperature: 400 degrees F. for 15 minutes



P99E039
14.4V 1500mAh Li-ion Cordless Caulking Gun

- Battery: 14.4V, Li-ion 1*1500mAh.
- Power of thrust: 220KG Speed choose button.
- Max capacity: 600ml.
- 1 hours charger.
- Simple design,easy portable.
- Plastic box packing.
- For Cartridge and Sausage pack
- CE approved



P99D135
Powder Coating Sprayers

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Line Cord: 6 feet long, 0.75mm2, 3-prong grounded plug
- Air Supply Pressure: 10 to 30 PSI
- Cubic Feet Per Minute: 3.5 CFM at 30 PSI
- Air Inlet Size: 1/4 inch
- Remote Activation Switch: 8 Feet long
- Gun Powder Lead: 7 feet, high voltage lead
- Grounding Cable: 8 feet long with ground clamp
- Control Box Fuse: 0.5 amps
- Paint Curing Temperature: 400 degrees F. for 15 minutes (recommended)



P99F051
300-CFM Air Blower

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Moves 300 cubic feet per minute of air up to 30 feet away
- 3-speed switch allows user to adjust air speed
- 4-position adjustment for concentrated air flow and fast drying
- Power:180w
- Speed:1600rPM
- CSA Approved



P99F052
300-CFM Air Blower

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Moves 300 cubic feet per minute of air up to 30 feet away
- 3-speed switch allows user to adjust air speed
- 4-position adjustment for concentrated air flow and fast drying
- Power:180w
- Speed:1600rPM
- CSA Approved



P99F525
345CFM-Air Blower 65W

- Rated Voltage/Frequency: 100V/50 or 100V/60Hz
- Power: 65W
- Volume: 345CFM
- Speeds: 1150rpm
- CE approved



P99H135
Electric engraver 13W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:13W
- No load Speed: 7200SPM
- 1.8m cable
- 1pc Tungsten carbide tip
- 2pc Stencil
- Use on metal, glass,wood,plastic
- GS/CETLus Approved



P99F055
1200-CFM Air Blower

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Moves 1,200 cubic feet per minute of air up to 30 feet away
- 3-speed switch allows user to adjust air speed
- 4-position adjustment for concentrated air flow and fast drying
- Power:320w
- Speed:1600rPM
- CSA Approved



P99F575
2500CFM-Air Blower 650W

- Rated Voltage/Frequency: 100V/50 or 100V/60Hz
- Power: 650W
- Volume: 2500CFM
- No load speed: 1200/1300/1400/rpm
- CE approved



P99I051G
Gasoline Pressure Washer

- Pump Model: brass pump
- Water Flow(gpm/lpm): 2.4/9.0
- Working Pressure(psi/bar):2175/150
- Max. Pressure(psi/bar):2700/186
- Pump Type: Swashplate pump
- Reated Rotational Sped(rpm): 3400
- Starting System:Recoil
- Displacement(cu.cm):163




P99F056
1200-CFM Air Blower

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Moves 1,200 cubic feet per minute of air up to 30 feet away
- 3-speed switch allows user to adjust air speed
- 4-position adjustment for concentrated air flow and fast drying
- Power:320w
- Speed:1600rPM
- CSA Approved



P99F935
Heater Attachment

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power:1320W
- 5000BTU
- Fits most 300CFM blower fans
- CSA Approved



P99I135
High Pressure Washer 5.5L/ min 1.5GMP 2000W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 2000W
- Working Pressure:1700psi
- Max. Pressure: 2000psi
- Temperature:Cold
- Motor:INDUCTION MOTOR
- Flow Rate: 5.5L/min
- CE Approved



P99I215 High Pressure Washer 6L/min (1.6GPM) 1400W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor type: Brush(Auto stop)
- Flow: 6L/min(1.6GPM)
- Working Pressure :60bar
- Max Pressure: 130bar
- Power:1400W
- Accessories: Pressure hose, Pressure gun,Soap bottle
- CE Approved



P99I216 High Pressure Washer 6L/min (1.6GPM) 1600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor type: Brush(Auto stop)
- Flow: 6L/min(1.6GPM)
- Power:1600W
- Working Pressure :70bar
- Max Pressure: 135bar
- Accessories: 5M Pressure hose, Pressure gun,Soap bottle
- CE Approved



P99I219 High Pressure Washer 6.4L/min (1.7GPM) 1600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Motor type: Brush(Auto stop)
- Flow: 6L/min(1.6GPM)
- Power:1600W
- Working Pressure :70bar
- Max Pressure: 135bar
- Accessories: 5M Pressure hose, Pressure gun,Soap bottle
- CE Approved



P99I223 High Pressure Washer 6L/ M 1600W

- Rated voltage/frequency: 120v-60hz / 230v-50hz
- Power:1600w
- Flow rate:6l/m
- 10.67m electric cable :awg14
- High pressure hose length:7m
- Accessories:jet-fan spray gun, pressure hose, soap Bottle,quick connector
- Max pressure:180bar,working pressure: 125bar (1800psi)
- Cetlus approved



P99I225 High Pressure Washer 6L/ Min 1600W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1600W
- Working Pressure: 85bar/1250psi
- Max Pressure: 130bar/1900psi
- Accessories: LDG03 Gun, 5M of Pressure Hose, 10.66M power cord, wheels and pulling rod
- Flow:6L/min
- CSA Approved



P99I227 High Pressure Washer 6L/ M 1600W

- Rated Voltage/frequency: 120v-60hz / 230v-50hz
- Power:1600w
- Flow Rate:6l/m
- 10.67m Electric Cable :awg14
- High Pressure Hose Length:7m
- Accessories:jet-fan Spray Gun, pressure Hose, soap Bottle,quick Connector
- max Pressure:180bar,working Pressure: 125bar (1800psi)
- Cetlus Approved



P99I327 High Pressure Washer 7L/ M 1900W

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Power: 1900W
- Working Pressure: 110bar/1600psi
- Max Pressure: 150bar/2200psi
- Accessories: LDG02A Gun, 7M of Pressure Hose, 10.66M power cord, built-in detergent bottle, plastic quick connector
- Flo: 7L/m
- CSA Approved



P99L125 Industrial Fan Heaters 2KW

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Heat output(W): 20/2000
- Air Output (M3/h): 180
- Noise(d/b): 40
- Heating element: Stainless steel
- Overheat protection,Full metal casing, Insulated handle more safe for using
- Waterproof class: IP23
- CE Approved



P99L145 Industrial Fan Heaters 3KW

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Heat output(W): 27/1500/3000
- Noise(d/b): 48
- Heating element: Stainless steel
- Outlet diameter(MM): 210
- Overheat protection,Full metal casing, Insulated handle more safe for using
- Waterproof class: IP23
- CE Approved



P99L165 Industrial Fan Heaters 3KW

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Heat output(W): 27/1500/3000
- Noise(d/b): 48
- Heating element: Stainless steel
- Outlet diameter(MM): 210
- Overheat protection,Full metal casing, Insulated handle more safe for using
- Waterproof class: IP23
- CE Approved



P99N110 Wet And Dry Vacuum Cleaner 1020W 15L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Vacuum: >17Kpa
- Capacity: 15L
- Air Flow(L/S): 28
- Noise: 82dB
- Material: Stainless steel, 0.4mm
- Al-Field & Copper-Amature, wet&dry
- With blow function at the horizontal direction
- GS Approved



P99N112 Wet And Dry Vacuum Cleaner 1020W 20L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Vacuum: >17Kpa
- Capacity: 20L
- Noise: < 78dB
- Wet and Dry two application motor, with long motor endurance life
- With blow function at the horizontal direction
- GS/cETLus Approved



P99N113 Wet And Dry Vacuum Cleaner 1020W 30L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Vacuum: >17Kpa
- Capacity: 30L
- Noise: < 78dB
- Wet and Dry two application motor, with long motor endurance life
- With blow function at the horizontal direction
- GS/cETLus Approved



P99N132 Wet And Dry Vacuum Cleaner 1020W 20L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Vacuum: >17Kpa
- Capacity: 20L
- Noise: < 78dB
- Wet and Dry two application motor, with long motor endurance life
- With blow function at the horizontal direction
- GS/cETLus Approved



P99N133 Wet And Dry Vacuum Cleaner 1020W 30L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Vacuum: >17Kpa
- Capacity: 30L
- Noise: < 78dB
- Wet and Dry two application motor, with long motor endurance life
- With blow function at the horizontal direction
- GS/cETLus Approved



P99N135 Wet And Dry Vacuum Cleaner 1020W 50L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Vacuum: >17Kpa
- Capacity: 50L
- Noise: < 78dB
- Wet and Dry two application motor, with long motor endurance life
- With blow function at the horizontal direction
- GS/cETLus Approved



P99N136 Wet And Dry Vacuum Cleaner 1020W 60L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Vacuum: >17Kpa
- Noise: < 78dB
- Wet and Dry two application motor, with long motor endurance life
- With blow function at the horizontal direction
- GS/cETLus Approved



P99N137 Wet And Dry Vacuum Cleaner 2400W 70L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Vacuum: >18Kpa
- Capacity: 70L
- Cord length: 4.5m
- Noise: < 78dB
- Material: Stainless steel
- 2 motors, strong performance
- GS/CE Approved



P99N232 Wet And Dry Vacuum Cleaner 1000W 20L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Tank diameter: 320mm
- Mode of cooling: Circulating air cooling
- Air folw rate: 53L/S
- Vacuity: ≥17KPa
- Noise: 70-72dB(A)
- Hose diameter: 38mm
- GS/CE Approved



P99N233 Wet And Dry Vacuum Cleaner 1000W 30L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Tank diameter: 320mm
- Mode of cooling: Circulating air cooling
- Air folw rate: 53L/S
- Vacuity: ≥17KPa
- Noise: 70-72dB(A)
- Hose length: 1.5m
- Cable length: 4.5m
- GS/CE Approved



P99N235 Wet And Dry Vacuum Cleaner 1000W 50L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Capacity: 50L
- Tank diameter: 350mm
- Mode of cooling: Circulating air cooling
- Air folw rate: 53L/S
- Vacuity: ≥17KPa
- Noise: 70-72dB(A)
- Hose diameter: 38mm
- Hose length: 1.5m
- GS/CE Approved



P99N238 Wet And Dry Vacuum Cleaner 3000W 80L

- Rated Voltage/Frequency: 120V-60Hz / 230V-50HZ
- Capacity: 80L
- Tank diameter: φ420mm
- Mode of cooling: Circulating air cooling
- Air flow rate: 108L/S
- Vacuity: ≥20KPa
- Noise: 76-78dB(A)
- Hose diameter: φ48mm
- GS/CE Approved



P99Z035 250MW Mini USB Laser Engraving Machine

- Power: 250MW
- 8x7.5cm carving area
- Carving of material: wood, bamboo, leather, cardboard, rubber, sheet stamp, paper, plastic
- Low noise
- Accessories: Power adapter, USB data line, protecting glasses

